






WWW.JJTOOLS.CO.KR
Made in Korea


 제이제이툴스(주)
JJ TOOLS Co.,Ltd.
(구) 장진공구

JJ series



Carbide End Mills INDEX

시리즈 Series	특징 Hardness	주문 번호 EDP. NO	형상 Appearance	날 수 Flutes	분류 Type	쪽 Page
JJ series 고경도용	고경도 고속 가공 HRc 52~70	2JJRB		2F	제이제이 리브 볼 JJ Rib Ball End Mills	08
		3JJRB	<i>New</i> 	3F	제이제이 리브 볼 JJ Rib Ball End Mills	11
		2JJTB		2F	제이제이 테이퍼 넥 볼 Taper Neck Ball End Mills	12
		3JJTBS	<i>New</i> 	3F	소비자 맞춤 테이퍼 넥 볼 Taper Neck Ball End Mills	16
		2JJSP		2F	3D 230° 가공용 구형 엔드밀 End Mills for 3D Cut 230°	17
		4JJSP		4F	3D 230° 가공용 구형 엔드밀 End Mills for 3D Cut 230°	18
		4JJSPM		4F	3D 270° 가공용 구형 엔드밀 End Mills for 3D Cut 270°	19
		2JJSB		2F	제이제이 짧은 길이 볼 JJ Short Length Ball End Mills	20
		2JJB		2F	제이제이 볼 JJ Ball End Mills	21
	고경도 고속 가공 HRc 52~65	2JJRE		2F	제이제이 리브 엔드밀 JJ Rib End Mills	22
		4JJRE		4F	제이제이 리브 엔드밀 JJ Rib End Mills	24
		2JJE		2F	제이제이 엔드밀 JJ End Mills	25
		4JJE		4F	제이제이 엔드밀 JJ End Mills	26
		4JJHE		4F	제이제이 45° 헬릭스 엔드밀 JJ 45° Helix End Mills	27
	고경도 고속 가공 HRc 52~70	6&8JJHE		6&8	제이제이 45° 헬릭스 엔드밀 JJ 45° Helix End Mills	28
		2JJCR		2F	제이제이 리브 코너 레디우스 JJ Rib Corner Radius	29
		2JJTC		2F	테이퍼 넥 코너 레디우스 Taper Neck Corner Radius	33
		4JJCR		4F	제이제이 리브 코너 레디우스 JJ Rib Corner Radius	35
		4JJTC		4F	테이퍼 넥 코너 레디우스 Taper Neck Corner Radius	38
		2JJC		2F	제이제이 코너 레디우스 JJ Corner Radius	39
		4JJC		4F	제이제이 코너 레디우스 JJ Corner Radius	41
		4&6JJRC		4&6	고이송 코너 레디우스 커터 High Speed Radius Cutter	43



0.05 ~ 2.5R 3 ~ 6R

- 고경도강(HRC52~70), 프리하든강 계열의 고정밀가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 날부인선의 조도가 뛰어나 피삭재의 면조도가 우수합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRC52~70)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Very nice work surface finish.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.

D Size	D Tolerance
Ø0.1	+0 ~ -0.005mm
Ø0.2 ~ 5	+0 ~ -0.01mm
Ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm


Order Number	날경 Diameter R x D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter R x D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
2JJRB 001 003 S04	0.05R X 0.1	0.3	-	40	4		2JJRB 006 020 S04	0.3R X 0.6	0.6	2	45	4	
2JJRB 001 005 S04	0.05R X 0.1	0.5	-	40	4		2JJRB 006 020 S06	0.3R X 0.6	0.6	2	50	6	
2JJRB 002 005 S04	0.1R X 0.2	0.2	0.5	40	4		2JJRB 006 030 S04	0.3R X 0.6	0.6	3	45	4	
2JJRB 002 010 S04	0.1R X 0.2	0.2	1	40	4		2JJRB 006 030 S06	0.3R X 0.6	0.6	3	50	6	
2JJRB 002 015 S04	0.1R X 0.2	0.2	1.5	40	4		2JJRB 006 040 S04	0.3R X 0.6	0.6	4	45	4	
2JJRB 002 020 S04	0.1R X 0.2	0.2	2	40	4		2JJRB 006 040 S06	0.3R X 0.6	0.6	4	50	6	
2JJRB 002 025 S04	0.1R X 0.2	0.2	2.5	40	4		2JJRB 006 050 S04	0.3R X 0.6	0.6	5	45	4	
2JJRB 002 030 S04	0.1R X 0.2	0.2	3	40	4		2JJRB 006 050 S06	0.3R X 0.6	0.6	5	50	6	
2JJRB 003 010 S04	0.15R X 0.3	0.3	1	40	4		2JJRB 006 060 S04	0.3R X 0.6	0.6	6	45	4	
2JJRB 003 015 S04	0.15R X 0.3	0.3	1.5	40	4		2JJRB 006 060 S06	0.3R X 0.6	0.6	6	50	6	
2JJRB 003 020 S04	0.15R X 0.3	0.3	2	40	4		2JJRB 006 080 S04	0.3R X 0.6	0.6	8	45	4	
2JJRB 003 025 S04	0.15R X 0.3	0.3	2.5	40	4		2JJRB 006 080 S06	0.3R X 0.6	0.6	8	50	6	
2JJRB 003 030 S04	0.15R X 0.3	0.3	3	40	4		2JJRB 006 100 S04	0.3R X 0.6	0.6	10	45	4	
2JJRB 003 035 S04	0.15R X 0.3	0.3	3.5	40	4		2JJRB 006 120 S04	0.3R X 0.6	0.6	12	45	4	
2JJRB 003 040 S04	0.15R X 0.3	0.3	4	40	4		2JJRB 006 140 S04	0.3R X 0.6	0.6	14	45	4	
2JJRB 003 050 S04	0.15R X 0.3	0.3	5	40	4		2JJRB 007 020 S04	0.35R X 0.7	0.7	2	45	4	
2JJRB 004 010 S04	0.2R X 0.4	0.4	1	40	4		2JJRB 007 040 S04	0.35R X 0.7	0.7	4	45	4	
2JJRB 004 015 S04	0.2R X 0.4	0.4	1.5	40	4		2JJRB 007 060 S04	0.35R X 0.7	0.7	6	45	4	
2JJRB 004 020 S04	0.2R X 0.4	0.4	2	40	4		2JJRB 007 080 S04	0.35R X 0.7	0.7	8	45	4	
2JJRB 004 025 S04	0.2R X 0.4	0.4	2.5	40	4		2JJRB 007 100 S04	0.35R X 0.7	0.7	10	45	4	
2JJRB 004 030 S04	0.2R X 0.4	0.4	3	40	4		2JJRB 007 120 S04	0.35R X 0.7	0.7	12	45	4	
2JJRB 004 035 S04	0.2R X 0.4	0.4	3.5	40	4		2JJRB 008 020 S04	0.4R X 0.8	0.8	2	45	4	
2JJRB 004 040 S04	0.2R X 0.4	0.4	4	40	4		2JJRB 008 020 S06	0.4R X 0.8	0.8	2	50	6	
2JJRB 004 045 S04	0.2R X 0.4	0.4	4.5	40	4		2JJRB 008 030 S04	0.4R X 0.8	0.8	3	45	4	
2JJRB 004 050 S04	0.2R X 0.4	0.4	5	40	4		2JJRB 008 030 S06	0.4R X 0.8	0.8	3	50	6	
2JJRB 004 060 S04	0.2R X 0.4	0.4	6	40	4		2JJRB 008 040 S04	0.4R X 0.8	0.8	4	45	4	
2JJRB 004 080 S04	0.2R X 0.4	0.4	8	40	4		2JJRB 008 040 S06	0.4R X 0.8	0.8	4	50	6	
2JJRB 005 010 S04	0.25R X 0.5	0.5	1	45	4		2JJRB 008 050 S04	0.4R X 0.8	0.8	5	45	4	
2JJRB 005 010 S06	0.25R X 0.5	0.5	1	50	6		2JJRB 008 050 S06	0.4R X 0.8	0.8	5	50	6	
2JJRB 005 015 S04	0.25R X 0.5	0.5	1.5	45	4		2JJRB 008 060 S04	0.4R X 0.8	0.8	6	45	4	
2JJRB 005 020 S04	0.25R X 0.5	0.5	2	45	4		2JJRB 008 060 S06	0.4R X 0.8	0.8	6	50	6	
2JJRB 005 020 S06	0.25R X 0.5	0.5	2	50	6		2JJRB 008 080 S04	0.4R X 0.8	0.8	8	45	4	
2JJRB 005 025 S04	0.25R X 0.5	0.5	2.5	45	4		2JJRB 008 080 S06	0.4R X 0.8	0.8	8	50	6	
2JJRB 005 030 S04	0.25R X 0.5	0.5	3	45	4		2JJRB 008 100 S04	0.4R X 0.8	0.8	10	45	4	
2JJRB 005 030 S06	0.25R X 0.5	0.5	3	50	6		2JJRB 008 120 S04	0.4R X 0.8	0.8	12	45	4	
2JJRB 005 035 S04	0.25R X 0.5	0.5	3.5	45	4		2JJRB 009 040 S04	0.45R X 0.9	0.9	4	45	4	
2JJRB 005 040 S04	0.25R X 0.5	0.5	4	45	4		2JJRB 009 060 S04	0.45R X 0.9	0.9	6	45	4	
2JJRB 005 040 S06	0.25R X 0.5	0.5	4	50	6		2JJRB 009 080 S04	0.45R X 0.9	0.9	8	45	4	
2JJRB 005 045 S04	0.25R X 0.5	0.5	4.5	45	4		2JJRB 009 100 S04	0.45R X 0.9	0.9	10	50	4	
2JJRB 005 050 S04	0.25R X 0.5	0.5	5	45	4		2JJRB 009 120 S04	0.45R X 0.9	0.9	12	50	4	
2JJRB 005 050 S06	0.25R X 0.5	0.5	5	50	6		2JJRB 010 020 S04	0.5R X 1	1	2	45	4	
2JJRB 005 060 S04	0.25R X 0.5	0.5	6	45	4		2JJRB 010 020 S06	0.5R X 1	1	2	50	6	
2JJRB 005 060 S06	0.25R X 0.5	0.5	6	50	6		2JJRB 010 030 S04	0.5R X 1	1	3	45	4	
2JJRB 005 080 S04	0.25R X 0.5	0.5	8	45	4		2JJRB 010 030 S06	0.5R X 1	1	3	50	6	
2JJRB 005 100 S04	0.25R X 0.5	0.5	10	45	4		2JJRB 010 040 S04	0.5R X 1	1	4	45	4	
2JJRB 005 120 S04	0.25R X 0.5	0.5	12	45	4		2JJRB 010 040 S06	0.5R X 1	1	4	50	6	
2JJRB 006 010 S04	0.3R X 0.6	0.6	1	45	4		2JJRB 010 050 S04	0.5R X 1	1	5	45	4	
2JJRB 006 010 S06	0.3R X 0.6	0.6	1	50	6		2JJRB 010 050 S06	0.5R X 1	1	5	50	6	

단위 : mm

Order Number	날경 Diameter R × D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter R × D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
2JJRB 010 060 S04	0.5R X 1	1	6	45	4		2JJRB 015 200 S04	0.75R X 1.5	1.5	20	50	4	
2JJRB 010 060 S06	0.5R X 1	1	6	50	6		2JJRB 015 220 S04	0.75R X 1.5	1.5	22	60	4	
2JJRB 010 080 S04	0.5R X 1	1	8	45	4		2JJRB 015 250 S04	0.75R X 1.5	1.5	25	60	4	
2JJRB 010 080 S06	0.5R X 1	1	8	50	6		2JJRB 015 300 S04	0.75R X 1.5	1.5	30	70	4	
2JJRB 010 100 S04	0.5R X 1	1	10	50	4		2JJRB 016 060 S04	0.8R X 1.6	1.6	6	45	4	
2JJRB 010 100 S06	0.5R X 1	1	10	50	6		2JJRB 016 080 S04	0.8R X 1.6	1.6	8	45	4	
2JJRB 010 120 S04	0.5R X 1	1	12	50	4		2JJRB 016 120 S04	0.8R X 1.6	1.6	12	50	4	
2JJRB 010 120 S06	0.5R X 1	1	12	50	6		2JJRB 016 160 S04	0.8R X 1.6	1.6	16	50	4	
2JJRB 010 140 S04	0.5R X 1	1	14	50	4		2JJRB 016 200 S04	0.8R X 1.6	1.6	20	50	4	
2JJRB 010 160 S04	0.5R X 1	1	16	50	4		2JJRB 018 060 S04	0.9R X 1.8	1.8	6	50	4	
2JJRB 010 180 S04	0.5R X 1	1	18	50	4		2JJRB 018 080 S04	0.9R X 1.8	1.8	8	50	4	
2JJRB 010 200 S04	0.5R X 1	1	20	50	4		2JJRB 018 120 S04	0.9R X 1.8	1.8	12	50	4	
2JJRB 010 220 S04	0.5R X 1	1	22	60	4		2JJRB 018 160 S04	0.9R X 1.8	1.8	16	50	4	
2JJRB 010 250 S04	0.5R X 1	1	25	60	4		2JJRB 018 200 S04	0.9R X 1.8	1.8	20	50	4	
2JJRB 012 040 S04	0.6R X 1.2	1.2	4	45	4		2JJRB 020 040 S04	1R X 2	2	4	45	4	
2JJRB 012 040 S06	0.6R X 1.2	1.2	4	50	6		2JJRB 020 040 S06	1R X 2	2	4	50	6	
2JJRB 012 060 S04	0.6R X 1.2	1.2	6	45	4		2JJRB 020 060 S04	1R X 2	2	6	45	4	
2JJRB 012 060 S06	0.6R X 1.2	1.2	6	50	6		2JJRB 020 060 S06	1R X 2	2	6	50	6	
2JJRB 012 080 S04	0.6R X 1.2	1.2	8	45	4		2JJRB 020 080 S04	1R X 2	2	8	45	4	
2JJRB 012 080 S06	0.6R X 1.2	1.2	8	50	6		2JJRB 020 080 S06	1R X 2	2	8	50	6	
2JJRB 012 100 S04	0.6R X 1.2	1.2	10	50	4		2JJRB 020 100 S04	1R X 2	2	10	50	4	
2JJRB 012 100 S06	0.6R X 1.2	1.2	10	50	6		2JJRB 020 100 S06	1R X 2	2	10	50	6	
2JJRB 012 120 S04	0.6R X 1.2	1.2	12	50	4		2JJRB 020 120 S04	1R X 2	2	12	50	4	
2JJRB 012 120 S06	0.6R X 1.2	1.2	12	50	6		2JJRB 020 120 S06	1R X 2	2	12	50	6	
2JJRB 012 160 S04	0.6R X 1.2	1.2	16	50	4		2JJRB 020 140 S04	1R X 2	2	14	50	4	
2JJRB 012 200 S04	0.6R X 1.2	1.2	20	50	4		2JJRB 020 140 S06	1R X 2	2	14	50	6	
2JJRB 012 240 S04	0.6R X 1.2	1.2	24	60	4		2JJRB 020 160 S04	1R X 2	2	16	50	4	
2JJRB 014 060 S04	0.7R X 1.4	1.4	6	45	4		2JJRB 020 160 S06	1R X 2	2	16	60	6	
2JJRB 014 080 S04	0.7R X 1.4	1.4	8	45	4		2JJRB 020 180 S04	1R X 2	2	18	50	4	
2JJRB 014 120 S04	0.7R X 1.4	1.4	12	50	4		2JJRB 020 180 S06	1R X 2	2	18	60	6	
2JJRB 014 160 S04	0.7R X 1.4	1.4	16	50	4		2JJRB 020 200 S04	1R X 2	2	20	50	4	
2JJRB 015 030 S04	0.75R X 1.5	1.5	3	45	4		2JJRB 020 200 S06	1R X 2	2	20	60	6	
2JJRB 015 030 S06	0.75R X 1.5	1.5	3	50	6		2JJRB 020 220 S04	1R X 2	2	22	60	4	
2JJRB 015 040 S04	0.75R X 1.5	1.5	4	45	4		2JJRB 020 250 S04	1R X 2	2	25	60	4	
2JJRB 015 040 S06	0.75R X 1.5	1.5	4	50	6		2JJRB 020 300 S04	1R X 2	2	30	60	4	
2JJRB 015 060 S04	0.75R X 1.5	1.5	6	45	4		2JJRB 025 080 S04	1.25R X 2.5	2.5	8	45	4	
2JJRB 015 060 S06	0.75R X 1.5	1.5	6	50	6		2JJRB 025 080 S06	1.25R X 2.5	2.5	8	50	6	
2JJRB 015 080 S04	0.75R X 1.5	1.5	8	45	4		2JJRB 025 100 S04	1.25R X 2.5	2.5	10	50	4	
2JJRB 015 080 S06	0.75R X 1.5	1.5	8	50	6		2JJRB 025 100 S06	1.25R X 2.5	2.5	10	50	6	
2JJRB 015 100 S04	0.75R X 1.5	1.5	10	50	4		New 2JJRB 025 120 S04	1.25R X 2.5	2.5	12	50	4	
2JJRB 015 100 S06	0.75R X 1.5	1.5	10	50	6		New 2JJRB 025 120 S06	1.25R X 2.5	2.5	12	50	6	
2JJRB 015 120 S04	0.75R X 1.5	1.5	12	50	4		2JJRB 025 160 S04	1.25R X 2.5	2.5	16	50	4	
2JJRB 015 120 S06	0.75R X 1.5	1.5	12	50	6		2JJRB 025 160 S06	1.25R X 2.5	2.5	16	60	6	
2JJRB 015 140 S04	0.75R X 1.5	1.5	14	50	4		2JJRB 025 200 S04	1.25R X 2.5	2.5	20	60	4	
2JJRB 015 140 S06	0.75R X 1.5	1.5	14	50	6		2JJRB 025 200 S06	1.25R X 2.5	2.5	20	60	6	
2JJRB 015 160 S04	0.75R X 1.5	1.5	16	50	4		2JJRB 025 250 S04	1.25R X 2.5	2.5	25	60	4	
2JJRB 015 160 S06	0.75R X 1.5	1.5	16	60	6		2JJRB 025 300 S04	1.25R X 2.5	2.5	30	70	4	
2JJRB 015 180 S04	0.75R X 1.5	1.5	18	50	4		2JJRB 030 060 S06	1.5R X 3	3	6	50	6	

단위 : mm

Order Number	날경 Diameter R x D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고										
2JJRB 030 080 S06	1.5R X 3	3	8	50	6											
2JJRB 030 100 S06	1.5R X 3	3	10	50	6											
2JJRB 030 120 S06	1.5R X 3	3	12	50	6											
2JJRB 030 160 S06	1.5R X 3	3	16	60	6											
2JJRB 030 200 S06	1.5R X 3	3	20	60	6											
2JJRB 030 250 S06	1.5R X 3	3	25	65	6											
2JJRB 030 300 S06	1.5R X 3	3	30	70	6											
2JJRB 030 350 S06	1.5R X 3	3	35	75	6											
2JJRB 030 400 S06	1.5R X 3	3	40	80	6											
2JJRB 030 450 S06	1.5R X 3	3	45	90	6											
New 2JJRB 030 500 S06	1.5R X 3	3	50	100	6											
2JJRB 035 100 S06	1.75R X 3.5	3.5	10	50	6											
2JJRB 035 150 S06	1.75R X 3.5	3.5	15	60	6											
2JJRB 035 200 S06	1.75R X 3.5	3.5	20	60	6											
2JJRB 035 250 S06	1.75R X 3.5	3.5	25	65	6											
2JJRB 035 300 S06	1.75R X 3.5	3.5	30	70	6											
2JJRB 035 350 S06	1.75R X 3.5	3.5	35	75	6											
2JJRB 035 400 S06	1.75R X 3.5	3.5	40	80	6											
2JJRB 040 080 S06	2R X 4	4	8	50	6											
2JJRB 040 100 S06	2R X 4	4	10	50	6											
2JJRB 040 120 S06	2R X 4	4	12	50	6											
2JJRB 040 160 S06	2R X 4	4	16	60	6											
2JJRB 040 200 S06	2R X 4	4	20	60	6											
2JJRB 040 250 S06	2R X 4	4	25	65	6											
2JJRB 040 300 S06	2R X 4	4	30	70	6											
2JJRB 040 350 S06	2R X 4	4	35	75	6											
2JJRB 040 400 S06	2R X 4	4	40	80	6											
2JJRB 040 450 S06	2R X 4	4	45	90	6											
New 2JJRB 040 500 S06	2R X 4	4	50	100	6											
2JJRB 050 160 S06	2.5R X 5	6	16	60	6											
2JJRB 050 200 S06	2.5R X 5	6	20	60	6											
2JJRB 050 250 S06	2.5R X 5	6	25	70	6											
2JJRB 050 300 S06	2.5R X 5	6	30	75	6											
2JJRB 050 400 S06	2.5R X 5	6	40	80	6											
2JJRB 050 450 S06	2.5R X 5	6	45	90	6											
New 2JJRB 050 500 S06	2.5R X 5	6	50	100	6											
2JJRB 060 150 S06	3R X 6	10	15	55	6											
New 2JJRB 060 300 100	3R X 6	10	30	100	6											
New 2JJRB 060 500 120	3R X 6	10	50	120	6											
2JJRB 080 250 060	4R X 8	12	25	60	8											
New 2JJRB 080 300 100	4R X 8	12	30	100	8											
New 2JJRB 080 600 120	4R X 8	12	60	120	8											
2JJRB 100 300 070	5R X 10	16	30	70	10											
New 2JJRB 100 450 100	5R X 10	16	45	100	10											
New 2JJRB 100 600 130	5R X 10	16	60	130	10											
2JJRB 120 300 075	6R X 12	18	30	75	12											
New 2JJRB 120 500 110	6R X 12	18	50	110	12											
New 2JJRB 120 600 130	6R X 12	18	60	130	12											



- 고경도강(HRC52~70), 프리하든강 계열의 고정밀가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 날부인선의 조도가 뛰어나 피삭재의 면조도가 우수합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRC52~70)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Very nice work surface finish.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.




0.5 ~ 1.25R 1.5 ~ 3R 4 ~ 6R

D Size	D Tolerance
Ø1 ~ 5	+0 ~ -0.01mm
Ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm

Order Number	날경 Diameter R x D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter R x D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
3JJRB 010 040 S04	0.5R X 1	1.2	4	50	4		3JJRB 120 350 075	6R X 12	18	35	75	12	
3JJRB 010 060 S04	0.5R X 1	1.2	6	50	4		3JJRB 120 600 110	6R X 12	18	60	110	12	
3JJRB 010 080 S04	0.5R X 1	1.2	8	50	4								
3JJRB 010 100 S04	0.5R X 1	1.2	10	50	4								
3JJRB 010 120 S04	0.5R X 1	1.2	12	50	4								
3JJRB 010 160 S04	0.5R X 1	1.2	16	50	4								
3JJRB 015 060 S04	0.75R X 1.5	1.8	6	50	4								
3JJRB 015 080 S04	0.75R X 1.5	1.8	8	50	4								
3JJRB 015 100 S04	0.75R X 1.5	1.8	10	50	4								
3JJRB 015 120 S04	0.75R X 1.5	1.8	12	50	4								
3JJRB 015 160 S04	0.75R X 1.5	1.8	16	50	4								
3JJRB 015 200 S04	0.75R X 1.5	1.8	20	60	4								
3JJRB 020 080 S04	1R X 2	2.4	8	50	4								
3JJRB 020 100 S04	1R X 2	2.4	10	50	4								
3JJRB 020 120 S04	1R X 2	2.4	12	50	4								
3JJRB 020 160 S04	1R X 2	2.4	16	50	4								
3JJRB 020 200 S04	1R X 2	2.4	20	60	4								
3JJRB 020 250 S04	1R X 2	2.4	25	70	4								
3JJRB 025 080 S04	1.25R X 2.5	3	8	50	4								
3JJRB 025 100 S04	1.25R X 2.5	3	10	50	4								
3JJRB 025 120 S04	1.25R X 2.5	3	12	50	4								
3JJRB 025 160 S04	1.25R X 2.5	3	16	50	4								
3JJRB 025 200 S04	1.25R X 2.5	3	20	60	4								
3JJRB 025 250 S04	1.25R X 2.5	3	25	70	4								
3JJRB 030 120 S06	1.5R X 3	3.6	12	60	6								
3JJRB 030 160 S06	1.5R X 3	3.6	16	60	6								
3JJRB 030 200 S06	1.5R X 3	3.6	20	65	6								
3JJRB 030 250 S06	1.5R X 3	3.6	25	70	6								
3JJRB 030 300 S06	1.5R X 3	3.6	30	75	6								
3JJRB 030 400 S06	1.5R X 3	3.6	40	90	6								
3JJRB 030 500 S06	1.5R X 3	3.6	50	100	6								
3JJRB 040 160 S06	2R X 4	4.8	16	60	6								
3JJRB 040 200 S06	2R X 4	4.8	20	65	6								
3JJRB 040 250 S06	2R X 4	4.8	25	70	6								
3JJRB 040 300 S06	2R X 4	4.8	30	75	6								
3JJRB 040 400 S06	2R X 4	4.8	40	90	6								
3JJRB 040 500 S06	2R X 4	4.8	50	100	6								
3JJRB 040 600 S06	2R X 4	4.8	60	110	6								
3JJRB 050 300 S06	2.5R X 5	6	30	75	6								
3JJRB 050 400 S06	2.5R X 5	6	40	90	6								
3JJRB 050 500 S06	2.5R X 5	6	50	100	6								
3JJRB 050 600 S06	2.5R X 5	6	60	110	6								
3JJRB 060 200 060	3R X 6	9	20	60	6								
3JJRB 060 300 090	3R X 6	9	30	90	6								
3JJRB 080 250 060	4R X 8	12	25	60	8								
3JJRB 080 400 100	4R X 8	12	40	100	8								
3JJRB 100 300 070	5R X 10	15	30	70	10								
3JJRB 100 500 110	5R X 10	15	50	110	10								



- 고경도강(HRC52~70), 프리하든강 계열의 고정밀가공 엔드밀
- 고품질 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 유효장을 테이퍼 설계하여 깊은 홈 작업시 목부파손 및 떨림을 최소화 하였습니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 초미립자 초경합금(0.2μm)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.

• Endmills for pre-hardened and hardened steel(HRC52~70)

- Good wear resistance by high quality Si-based PVD coating.
- Minimize chattering and fracturing by taper designed flute.
- High precise edge tolerance.
- Outstanding performance at high speed machining by ultra fine (0.2 μm) WC grade.



0.1 ~ 2.5R 3 ~ 6R

D Size	D Tolerance
Ø0.2 ~ 5	+0 ~ -0.01mm
Ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm

Order Number	날경 Diameter R x D	각도 Angle θ	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter R x D	각도 Angle θ	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
2JJTB 002 003 015	0.1R X 0.2	0°30'	0.2	1.5	40	4		2JJTB 004 020 020	0.2R X 0.4	2°	0.4	2	40	4	
2JJTB 002 003 020	0.1R X 0.2	0°30'	0.2	2	40	4		2JJTB 004 020 030	0.2R X 0.4	2°	0.4	3	40	4	
2JJTB 002 010 015	0.1R X 0.2	1°	0.2	1.5	40	4		2JJTB 004 020 040	0.2R X 0.4	2°	0.4	4	40	4	
2JJTB 002 010 020	0.1R X 0.2	1°	0.2	2	40	4		2JJTB 004 020 050	0.2R X 0.4	2°	0.4	5	40	4	
2JJTB 002 010 025	0.1R X 0.2	1°	0.2	2.5	40	4		2JJTB 004 020 060	0.2R X 0.4	2°	0.4	6	40	4	
2JJTB 002 013 015	0.1R X 0.2	1°30'	0.2	1.5	40	4		2JJTB 005 003 040	0.25R X 0.5	0°30'	0.5	4	45	4	
2JJTB 002 013 020	0.1R X 0.2	1°30'	0.2	2	40	4		2JJTB 005 003 060	0.25R X 0.5	0°30'	0.5	6	45	4	
2JJTB 002 013 025	0.1R X 0.2	1°30'	0.2	2.5	40	4		2JJTB 005 010 040	0.25R X 0.5	1°	0.5	4	45	4	
2JJTB 002 020 015	0.1R X 0.2	2°	0.2	1.5	40	4		2JJTB 005 010 060	0.25R X 0.5	1°	0.5	6	45	4	
2JJTB 002 020 020	0.1R X 0.2	2°	0.2	2	40	4		2JJTB 005 010 080	0.25R X 0.5	1°	0.5	8	45	4	
2JJTB 002 020 025	0.1R X 0.2	2°	0.2	2.5	40	4		2JJTB 005 010 100	0.25R X 0.5	1°	0.5	10	45	4	
2JJTB 002 030 015	0.1R X 0.2	3°	0.2	1.5	40	4		2JJTB 005 013 040	0.25R X 0.5	1°30'	0.5	4	45	4	
2JJTB 002 030 020	0.1R X 0.2	3°	0.2	2	40	4		2JJTB 005 013 060	0.25R X 0.5	1°30'	0.5	6	45	4	
2JJTB 002 030 025	0.1R X 0.2	3°	0.2	2.5	40	4		2JJTB 005 013 080	0.25R X 0.5	1°30'	0.5	8	45	4	
2JJTB 002 050 020	0.1R X 0.2	5°	0.2	2	40	4		2JJTB 005 013 100	0.25R X 0.5	1°30'	0.5	10	45	4	
2JJTB 003 003 030	0.15R X 0.3	0°30'	0.3	3	40	4		2JJTB 005 020 040	0.25R X 0.5	2°	0.5	4	45	4	
2JJTB 003 010 020	0.15R X 0.3	1°	0.3	2	40	4		2JJTB 005 020 060	0.25R X 0.5	2°	0.5	6	45	4	
2JJTB 003 010 030	0.15R X 0.3	1°	0.3	3	40	4		2JJTB 005 020 080	0.25R X 0.5	2°	0.5	8	45	4	
2JJTB 003 010 040	0.15R X 0.3	1°	0.3	4	40	4		2JJTB 005 020 100	0.25R X 0.5	2°	0.5	10	45	4	
2JJTB 003 010 050	0.15R X 0.3	1°	0.3	5	40	4		2JJTB 005 030 080	0.25R X 0.5	3°	0.5	8	45	4	
2JJTB 003 013 020	0.15R X 0.3	1°30'	0.3	2	40	4		2JJTB 005 030 120	0.25R X 0.5	3°	0.5	12	50	4	
2JJTB 003 013 030	0.15R X 0.3	1°30'	0.3	3	40	4		New 2JJTB 005 030 200	0.25R X 0.5	3°	0.5	20	60	4	
2JJTB 003 013 040	0.15R X 0.3	1°30'	0.3	4	40	4		2JJTB 006 003 040	0.3R X 0.6	0°30'	0.6	4	45	4	
2JJTB 003 013 050	0.15R X 0.3	1°30'	0.3	5	40	4		2JJTB 006 003 060	0.3R X 0.6	0°30'	0.6	6	45	4	
2JJTB 003 020 020	0.15R X 0.3	2°	0.3	2	40	4		2JJTB 006 003 080	0.3R X 0.6	0°30'	0.6	8	45	4	
2JJTB 003 020 030	0.15R X 0.3	2°	0.3	3	40	4		2JJTB 006 010 040	0.3R X 0.6	1°	0.6	4	45	4	
2JJTB 003 020 040	0.15R X 0.3	2°	0.3	4	40	4		2JJTB 006 010 060	0.3R X 0.6	1°	0.6	6	45	4	
2JJTB 003 020 050	0.15R X 0.3	2°	0.3	5	40	4		2JJTB 006 010 080	0.3R X 0.6	1°	0.6	8	45	4	
2JJTB 003 030 020	0.15R X 0.3	3°	0.3	2	40	4		2JJTB 006 010 100	0.3R X 0.6	1°	0.6	10	45	4	
2JJTB 003 030 030	0.15R X 0.3	3°	0.3	3	40	4		2JJTB 006 010 120	0.3R X 0.6	1°	0.6	12	50	4	
2JJTB 003 030 040	0.15R X 0.3	3°	0.3	4	40	4		2JJTB 006 010 150	0.3R X 0.6	1°	0.6	15	50	4	
2JJTB 003 030 050	0.15R X 0.3	3°	0.3	5	40	4		New 2JJTB 006 010 200	0.3R X 0.6	1°	0.6	20	60	4	
2JJTB 003 050 050	0.15R X 0.3	5°	0.3	5	40	4		2JJTB 006 013 040	0.3R X 0.6	1°30'	0.6	4	45	4	
2JJTB 004 003 020	0.2R X 0.4	0°30'	0.4	2	40	4		2JJTB 006 013 060	0.3R X 0.6	1°30'	0.6	6	45	4	
2JJTB 004 003 030	0.2R X 0.4	0°30'	0.4	3	40	4		2JJTB 006 013 080	0.3R X 0.6	1°30'	0.6	8	45	4	
2JJTB 004 003 040	0.2R X 0.4	0°30'	0.4	4	40	4		2JJTB 006 013 100	0.3R X 0.6	1°30'	0.6	10	45	4	
2JJTB 004 003 050	0.2R X 0.4	0°30'	0.4	5	40	4		2JJTB 006 013 120	0.3R X 0.6	1°30'	0.6	12	50	4	
2JJTB 004 003 060	0.2R X 0.4	0°30'	0.4	6	40	4		New 2JJTB 006 013 150	0.3R X 0.6	1°30'	0.6	15	50	4	
2JJTB 004 010 020	0.2R X 0.4	1°	0.4	2	40	4		New 2JJTB 006 013 200	0.3R X 0.6	1°30'	0.6	20	60	4	
2JJTB 004 010 030	0.2R X 0.4	1°	0.4	3	40	4		2JJTB 006 020 060	0.3R X 0.6	2°	0.6	6	45	4	
2JJTB 004 010 040	0.2R X 0.4	1°	0.4	4	40	4		2JJTB 006 020 080	0.3R X 0.6	2°	0.6	8	45	4	
2JJTB 004 010 050	0.2R X 0.4	1°	0.4	5	40	4		2JJTB 006 020 100	0.3R X 0.6	2°	0.6	10	45	4	
2JJTB 004 010 060	0.2R X 0.4	1°	0.4	6	40	4		New 2JJTB 006 020 150	0.3R X 0.6	2°	0.6	15	50	4	
2JJTB 004 013 020	0.2R X 0.4	1°30'	0.4	2	40	4		New 2JJTB 006 020 200	0.3R X 0.6	2°	0.6	20	60	4	
2JJTB 004 013 030	0.2R X 0.4	1°30'	0.4	3	40	4		2JJTB 006 030 130	0.3R X 0.6	3°	0.6	13	50	4	
2JJTB 004 013 040	0.2R X 0.4	1°30'	0.4	4	40	4		New 2JJTB 006 030 200	0.3R X 0.6	3°	0.6	20	60	4	
2JJTB 004 013 050	0.2R X 0.4	1°30'	0.4	5	40	4		2JJTB 008 003 040	0.4R X 0.8	0°30'	0.8	4	45	4	
2JJTB 004 013 060	0.2R X 0.4	1°30'	0.4	6	40	4		2JJTB 008 003 060	0.4R X 0.8	0°30'	0.8	6	45	4	



Order Number	날경 Diameter R x D	각도 Angle θ	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Dia d	비고
2JJTB 008 003 080	0.4R X 0.8	0°30	0.8	8	45	4	
2JJTB 008 003 100	0.4R X 0.8	0°30	0.8	10	45	4	
2JJTB 008 003 120	0.4R X 0.8	0°30	0.8	12	50	4	
New 2JJTB 008 003 150	0.4R X 0.8	0°30	0.8	15	50	4	
New 2JJTB 008 003 200	0.4R X 0.8	0°30	0.8	20	60	4	
2JJTB 008 010 040	0.4R X 0.8	1°	0.8	4	45	4	
2JJTB 008 010 060	0.4R X 0.8	1°	0.8	6	45	4	
2JJTB 008 010 080	0.4R X 0.8	1°	0.8	8	45	4	
2JJTB 008 010 100	0.4R X 0.8	1°	0.8	10	45	4	
2JJTB 008 010 120	0.4R X 0.8	1°	0.8	12	50	4	
2JJTB 008 010 160	0.4R X 0.8	1°	0.8	16	50	4	
New 2JJTB 008 010 200	0.4R X 0.8	1°	0.8	20	60	4	
2JJTB 008 013 040	0.4R X 0.8	1°30	0.8	4	45	4	
2JJTB 008 013 060	0.4R X 0.8	1°30	0.8	6	45	4	
2JJTB 008 013 080	0.4R X 0.8	1°30	0.8	8	45	4	
2JJTB 008 013 100	0.4R X 0.8	1°30	0.8	10	45	4	
2JJTB 008 013 120	0.4R X 0.8	1°30	0.8	12	50	4	
2JJTB 008 013 160	0.4R X 0.8	1°30	0.8	16	50	4	
New 2JJTB 008 013 200	0.4R X 0.8	1°30	0.8	20	60	4	
2JJTB 008 020 080	0.4R X 0.8	2°	0.8	8	50	4	
2JJTB 008 020 100	0.4R X 0.8	2°	0.8	10	50	4	
2JJTB 008 020 120	0.4R X 0.8	2°	0.8	12	50	4	
2JJTB 008 020 160	0.4R X 0.8	2°	0.8	16	50	4	
New 2JJTB 008 020 200	0.4R X 0.8	2°	0.8	20	60	4	
2JJTB 008 030 080	0.4R X 0.8	3°	0.8	8	50	4	
2JJTB 008 030 120	0.4R X 0.8	3°	0.8	12	50	4	
2JJTB 008 030 160	0.4R X 0.8	3°	0.8	16	50	4	
New 2JJTB 008 030 200	0.4R X 0.8	3°	0.8	20	60	4	
2JJTB 010 003 060	0.5R X 1	0°30	1	6	50	4	
2JJTB 010 003 080	0.5R X 1	0°30	1	8	50	4	
2JJTB 010 003 100	0.5R X 1	0°30	1	10	50	4	
2JJTB 010 003 150	0.5R X 1	0°30	1	15	50	4	
2JJTB 010 003 200	0.5R X 1	0°30	1	20	60	4	
2JJTB 010 003 250	0.5R X 1	0°30	1	25	60	4	
2JJTB 010 003 300	0.5R X 1	0°30	1	30	70	4	
2JJTB 010 010 060	0.5R X 1	1°	1	6	50	4	
2JJTB 010 010 080	0.5R X 1	1°	1	8	50	4	
2JJTB 010 010 100	0.5R X 1	1°	1	10	50	4	
2JJTB 010 010 150	0.5R X 1	1°	1	15	50	4	
2JJTB 010 010 200	0.5R X 1	1°	1	20	50	4	
2JJTB 010 010 250	0.5R X 1	1°	1	25	60	4	
2JJTB 010 010 300	0.5R X 1	1°	1	30	70	4	
2JJTB 010 010 350	0.5R X 1	1°	1	35	75	4	
2JJTB 010 013 060	0.5R X 1	1°30	1	6	50	4	
2JJTB 010 013 080	0.5R X 1	1°30	1	8	50	4	
2JJTB 010 013 100	0.5R X 1	1°30	1	10	50	4	
2JJTB 010 013 150	0.5R X 1	1°30	1	15	50	4	
2JJTB 010 013 200	0.5R X 1	1°30	1	20	50	4	

Order Number	날경 Diameter R x D	각도 Angle θ	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Dia d	비고
2JJTB 010 013 250	0.5R X 1	1°30	1	25	60	4	
2JJTB 010 013 300	0.5R X 1	1°30	1	30	70	4	
New 2JJTB 010 013 350	0.5R X 1	1°30	1	35	80	4	
New 2JJTB 010 013 400	0.5R X 1	1°30	1	40	80	4	
2JJTB 010 020 150	0.5R X 1	2°	1	15	50	4	
2JJTB 010 020 200	0.5R X 1	2°	1	20	50	4	
2JJTB 010 020 250	0.5R X 1	2°	1	25	60	4	
2JJTB 010 020 300	0.5R X 1	2°	1	30	70	4	
New 2JJTB 010 020 400	0.5R X 1	2°	1	40	80	4	
2JJTB 010 030 200	0.5R X 1	3°	1	20	50	4	
2JJTB 010 030 300	0.5R X 1	3°	1	30	70	6	
2JJTB 010 030 400	0.5R X 1	3°	1	40	80	6	
New 2JJTB 010 030 500	0.5R X 1	3°	1	50	90	6	
2JJTB 010 050 230	0.5R X 1	5°	1	23	60	6	
2JJTB 012 003 080	0.6R X 1.2	0°30	1.2	8	50	4	
2JJTB 012 003 120	0.6R X 1.2	0°30	1.2	12	50	4	
2JJTB 012 003 180	0.6R X 1.2	0°30	1.2	18	50	4	
2JJTB 012 003 240	0.6R X 1.2	0°30	1.2	24	60	4	
2JJTB 012 010 080	0.6R X 1.2	1°	1.2	8	50	4	
2JJTB 012 010 120	0.6R X 1.2	1°	1.2	12	50	4	
2JJTB 012 010 180	0.6R X 1.2	1°	1.2	18	50	4	
2JJTB 012 010 240	0.6R X 1.2	1°	1.2	24	60	4	
2JJTB 012 013 080	0.6R X 1.2	1°30	1.2	8	50	4	
2JJTB 012 013 120	0.6R X 1.2	1°30	1.2	12	50	4	
2JJTB 012 013 180	0.6R X 1.2	1°30	1.2	18	50	4	
2JJTB 012 013 240	0.6R X 1.2	1°30	1.2	24	60	4	
2JJTB 012 020 080	0.6R X 1.2	2°	1.2	8	50	4	
2JJTB 012 020 120	0.6R X 1.2	2°	1.2	12	50	4	
2JJTB 012 020 180	0.6R X 1.2	2°	1.2	18	50	4	
2JJTB 012 020 240	0.6R X 1.2	2°	1.2	24	60	4	
2JJTB 015 003 080	0.75R X 1.5	0°30	1.5	8	50	4	
2JJTB 015 003 100	0.75R X 1.5	0°30	1.5	10	50	4	
2JJTB 015 003 120	0.75R X 1.5	0°30	1.5	12	50	4	
2JJTB 015 003 150	0.75R X 1.5	0°30	1.5	15	50	4	
2JJTB 015 003 200	0.75R X 1.5	0°30	1.5	20	60	4	
2JJTB 015 003 300	0.75R X 1.5	0°30	1.5	30	70	4	
New 2JJTB 015 003 400	0.75R X 1.5	0°30	1.5	40	80	4	
2JJTB 015 010 080	0.75R X 1.5	1°	1.5	8	50	4	
2JJTB 015 010 100	0.75R X 1.5	1°	1.5	10	50	4	
2JJTB 015 010 120	0.75R X 1.5	1°	1.5	12	50	4	
2JJTB 015 010 150	0.75R X 1.5	1°	1.5	15	50	4	
2JJTB 015 010 200	0.75R X 1.5	1°	1.5	20	60	4	
2JJTB 015 010 250	0.75R X 1.5	1°	1.5	25	60	4	
2JJTB 015 010 300	0.75R X 1.5	1°	1.5	30	70	4	
New 2JJTB 015 010 400	0.75R X 1.5	1°	1.5	40	80	4	
New 2JJTB 015 010 500	0.75R X 1.5	1°	1.5	50	90	4	
2JJTB 015 013 080	0.75R X 1.5	1°30	1.5	8	50	4	
2JJTB 015 013 100	0.75R X 1.5	1°30	1.5	10	50	4	

Order Number	날경 Diameter R x D	각도 Angle θ	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	생크 Shank Dia d	비고	Order Number	날경 Diameter R x D	각도 Angle θ	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	생크 Shank Dia d	비고
2JJTB 015 013 120	0.75R X 1.5	1°30'	1.5	12	50	4		2JJTB 020 050 250	1R X 2	5°	2	25	60	6	
2JJTB 015 013 150	0.75R X 1.5	1°30'	1.5	15	50	4		2JJTB 020 050 380	1R X 2	5°	2	38	80	8	
2JJTB 015 013 200	0.75R X 1.5	1°30'	1.5	20	60	4		2JJTB 030 003 160	1.5R X 3	0°30'	3	16	60	6	
2JJTB 015 013 250	0.75R X 1.5	1°30'	1.5	25	60	4		2JJTB 030 003 200	1.5R X 3	0°30'	3	20	65	6	
2JJTB 015 013 300	0.75R X 1.5	1°30'	1.5	30	70	4		2JJTB 030 003 300	1.5R X 3	0°30'	3	30	70	6	
New 2JJTB 015 013 400	0.75R X 1.5	1°30'	1.5	40	80	4		2JJTB 030 003 400	1.5R X 3	0°30'	3	40	80	6	
New 2JJTB 015 013 500	0.75R X 1.5	1°30'	1.5	50	90	4		2JJTB 030 003 500	1.5R X 3	0°30'	3	50	90	6	
2JJTB 015 020 100	0.75R X 1.5	2°	1.5	10	50	4		New 2JJTB 030 003 600	1.5R X 3	0°30'	3	60	100	6	
2JJTB 015 020 150	0.75R X 1.5	2°	1.5	15	50	4		2JJTB 030 010 160	1.5R X 3	1°	3	16	60	6	
2JJTB 015 020 200	0.75R X 1.5	2°	1.5	20	60	4		2JJTB 030 010 200	1.5R X 3	1°	3	20	65	6	
2JJTB 015 020 300	0.75R X 1.5	2°	1.5	30	70	4		2JJTB 030 010 300	1.5R X 3	1°	3	30	70	6	
New 2JJTB 015 020 400	0.75R X 1.5	2°	1.5	40	80	6		2JJTB 030 010 400	1.5R X 3	1°	3	40	80	6	
New 2JJTB 015 020 500	0.75R X 1.5	2°	1.5	50	90	6		2JJTB 030 010 500	1.5R X 3	1°	3	50	90	6	
2JJTB 015 030 420	0.75R X 1.5	3°	1.5	42	80	6		New 2JJTB 030 010 600	1.5R X 3	1°	3	60	100	6	
2JJTB 015 050 250	0.75R X 1.5	5°	1.5	25	70	6		New 2JJTB 030 010 700	1.5R X 3	1°	3	70	110	6	
2JJTB 020 003 080	1R X 2	0°30'	2	8	50	4		2JJTB 030 013 160	1.5R X 3	1°30'	3	16	60	6	
2JJTB 020 003 120	1R X 2	0°30'	2	12	50	4		2JJTB 030 013 200	1.5R X 3	1°30'	3	20	65	6	
2JJTB 020 003 160	1R X 2	0°30'	2	16	50	4		2JJTB 030 013 300	1.5R X 3	1°30'	3	30	70	6	
2JJTB 020 003 200	1R X 2	0°30'	2	20	60	4		2JJTB 030 013 400	1.5R X 3	1°30'	3	40	80	6	
2JJTB 020 003 300	1R X 2	0°30'	2	30	70	4		2JJTB 030 013 500	1.5R X 3	1°30'	3	50	90	6	
2JJTB 020 003 400	1R X 2	0°30'	2	40	80	4		New 2JJTB 030 013 600	1.5R X 3	1°30'	3	60	100	6	
New 2JJTB 020 003 500	1R X 2	0°30'	2	50	90	4		New 2JJTB 030 013 700	1.5R X 3	1°30'	3	70	120	8	
2JJTB 020 010 080	1R X 2	1°	2	8	50	4		2JJTB 030 020 160	1.5R X 3	2°	3	16	60	6	
2JJTB 020 010 120	1R X 2	1°	2	12	50	4		2JJTB 030 020 200	1.5R X 3	2°	3	20	65	6	
2JJTB 020 010 160	1R X 2	1°	2	16	50	4		2JJTB 030 020 300	1.5R X 3	2°	3	30	70	6	
2JJTB 020 010 200	1R X 2	1°	2	20	60	4		2JJTB 030 020 480	1.5R X 3	2°	3	48	90	6	
2JJTB 020 010 250	1R X 2	1°	2	25	60	4		New 2JJTB 030 020 600	1.5R X 3	2°	3	60	110	8	
2JJTB 020 010 300	1R X 2	1°	2	30	70	4		New 2JJTB 030 020 700	1.5R X 3	2°	3	70	120	8	
2JJTB 020 010 350	1R X 2	1°	2	35	75	4		2JJTB 030 030 300	1.5R X 3	3°	3	30	70	6	
2JJTB 020 010 400	1R X 2	1°	2	40	80	4		2JJTB 030 030 500	1.5R X 3	3°	3	50	90	8	
2JJTB 020 010 500	1R X 2	1°	2	50	90	4		New 2JJTB 030 030 700	1.5R X 3	3°	3	70	120	10	
New 2JJTB 020 010 600	1R X 2	1°	2	60	100	6		2JJTB 030 050 330	1.5R X 3	5°	3	33	90	6	
2JJTB 020 013 080	1R X 2	1°30'	2	8	50	4		2JJTB 040 003 600	2R X 4	0°30'	4	60	100	6	
2JJTB 020 013 120	1R X 2	1°30'	2	12	50	4		New 2JJTB 040 003 700	2R X 4	0°30'	4	70	110	6	
2JJTB 020 013 160	1R X 2	1°30'	2	16	50	4		New 2JJTB 040 003 900	2R X 4	0°30'	4	90	130	6	
2JJTB 020 013 200	1R X 2	1°30'	2	20	60	4		2JJTB 040 010 500	2R X 4	1°	4	50	90	6	
2JJTB 020 013 250	1R X 2	1°30'	2	25	60	4		2JJTB 040 010 600	2R X 4	1°	4	60	100	6	
2JJTB 020 013 300	1R X 2	1°30'	2	30	70	4		New 2JJTB 040 010 700	2R X 4	1°	4	70	120	8	
2JJTB 020 013 350	1R X 2	1°30'	2	35	75	6		New 2JJTB 040 010 900	2R X 4	1°	4	90	150	8	
2JJTB 020 013 400	1R X 2	1°30'	2	40	80	6		2JJTB 040 013 450	2R X 4	1°30'	4	45	90	6	
2JJTB 020 013 500	1R X 2	1°30'	2	50	90	6		2JJTB 040 013 600	2R X 4	1°30'	4	60	110	8	
New 2JJTB 020 013 600	1R X 2	1°30'	2	60	100	6		New 2JJTB 040 013 700	2R X 4	1°30'	4	70	120	8	
2JJTB 020 020 300	1R X 2	2°	2	30	70	6		2JJTB 040 030 250	2R X 4	3°	4	25	70	6	
2JJTB 020 020 400	1R X 2	2°	2	40	80	6		New 2JJTB 040 030 420	2R X 4	3°	4	42	100	8	
2JJTB 020 020 500	1R X 2	2°	2	50	90	6		2JJTB 040 050 290	2R X 4	5°	4	29	90	8	
2JJTB 020 030 300	1R X 2	3°	2	30	70	6		New 2JJTB 050 010 400	2.5R X 5	1°	5	40	90	8	
2JJTB 020 030 400	1R X 2	3°	2	40	80	6		New 2JJTB 050 010 600	2.5R X 5	1°	5	60	110	8	
New 2JJTB 020 030 500	1R X 2	3°	2	50	90	6		New 2JJTB 050 010 900	2.5R X 5	1°	5	90	150	8	

단위 : mm


[illegible]



- **고경도강(HRC52~70), 프리하든강 계열의 고정밀가공 엔드밀**
- 고탄량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- **깊은 홀 가공이 빈번해진 추세에 맞춰, 고객 요구에 발빠르게 대응하는 맞춤형 제작 방식입니다. (최고 2일안에 납품 가능)**
- 고객주문에 맞춰, 자사 재고품의 각도 및 유효길이를 재조정 가공합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- **Endmills for pre-hardened and hardened steel(HRC52~70)**
- Good wear resistance by high quality Si-based PVD coating.
- In accordance with the recent trend of frequent deep hole machining, It is an order to make system responding to customer' quick delivery request. (within a 2 days)
- In accordance with the customer order, readjust the angle and effective length of own stock
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.

단위 : mm

[illegible]




- **고경도강(HRC52~70), 프리하든강 계열의 고정밀가공 엔드밀**
- 고풍량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 230도 구형의 인선으로 광범위한 3D 가공이 가능합니다.
- 유효장을 직선 및 테이퍼 설계하여 다양한 상황에 맞춰 목부파손 및 떨림을 최소화 하였습니다.
- 초미립자 초경합금($0.2\mu\text{m}$)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- **Endmills for pre-hardened and hardened steel(HRC52~70)**
- Good wear resistance by high quality Si-based PVD coating.
- 230°degree ball shape for wide range 3D machining.
- Minimize chattering and fracturing by taper and straight designed flute.
- Outstanding performance at high speed machining by ultra fine ($0.2\mu\text{m}$) WC grade.

D Size	D Tolerance
ø1 ~ 5	+0 ~ -0.01mm
ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm

[illegible]

4날 제이제이3D 230도 가공용 구형 엔드밀




- **고경도강(HRC52~70), 프리하트강 계열의 고정밀가공 엔드밀**
- 고풍량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 230도 구형의 인선으로 광범위한 3D 가공이 가능합니다.
- 유효장을 직선 및 테이퍼 설계하여 다양한 상황에 맞춰 목부파손 및 떨림을 최소화 하였습니다.
- 초미립자 초경합금($0.2\mu\text{m}$)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- **Endmills for pre-hardened and hardened steel(HRC52~70)**
- Good wear resistance by high quality Si-based PVD coating.
- 230°degree ball shape for wide range 3D machining.
- Minimize chattering and fracturing by taper and straight designed flute.
- Outstanding performance at high speed machining by ultra fine ($0.2\mu\text{m}$) WC grade.

D Size	D Tolerance
ø1 ~ 5	+0 ~ -0.01mm
ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm

[illegible]




- **고경도강(HRC52~70), 프리하든강 계열의 고정밀가공 엔드밀**
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 270도 구형의 인선으로 광범위한 3D 가공이 가능합니다.
- 유효장을 직선 및 테이퍼 설계하여 다양한 상황에 맞춰 목부파손 및 떨림을 최소화 하였습니다.
- 초미립자 초경합금($0.2\mu\text{m}$)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- **Endmills for pre-hardened and hardened steel(HRC52~70)**
- Good wear resistance by high quality Si-based PVD coating.
- 270°degree ball shape for wide range 3D machining.
- Minimize chattering and fracturing by taper and straight designed flute.
- Outstanding performance at high speed machining by ultra fine ($0.2\mu\text{m}$) WC grade.

D Size	D Tolerance
ø1 ~ 5	+0 ~ -0.01mm
ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm

[illegible]

2날 고정도재 가공용 제이제이 짧은 길이 볼 엔드밀




- 고정도강(HRc52~70), 프리하트강 계열의 고정밀가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 짧은 전장을 채택하여 열박음척 사용이 용이합니다.
- 날부인선의 조도가 뛰어나 피삭재의 면조도가 우수합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel (HRc52~70)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Short overall length for easy use with shrinking chuck
- Very nice work surface finish.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.

D Size	D Tolerance
Ø0.1 ~ 0.15	+0 ~ -0.005mm
Ø0.2 ~ 5	+0 ~ -0.01mm
Ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm

Order Number	날경 Diameter R x D	날장 Length of cut L1	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter R x D	날장 Length of cut L1	전장 Overall Length L	샙크 Shank Dia d	비고
2JJSB 001 001 S04	0.05R X 0.1	0.1	40	4		2JJSB 120 120 060	6R X 12	12	60	12	
2JJSB 001 0015 S04	0.05R X 0.1	0.15	40	4		2JJSB 120 150 060	6R X 12	15	60	12	
2JJSB 0015 0015 S04	0.075R X 0.15	0.15	40	4							
2JJSB 0015 002 S04	0.075R X 0.15	0.2	40	4							
2JJSB 002 002 S04	0.1R X 0.2	0.2	40	4							
2JJSB 002 003 S04	0.1R X 0.2	0.3	40	4							
2JJSB 003 003 S04	0.15R X 0.3	0.3	40	4							
2JJSB 003 0045 S04	0.15R X 0.3	0.45	40	4							
2JJSB 004 004 S04	0.2R X 0.4	0.4	40	4							
2JJSB 004 006 S04	0.2R X 0.4	0.6	40	4							
2JJSB 005 005 S04	0.25R X 0.5	0.5	40	4							
2JJSB 005 0075 S04	0.25R X 0.5	0.75	40	4							
2JJSB 006 006 S04	0.3R X 0.6	0.6	40	4							
2JJSB 006 009 S04	0.3R X 0.6	0.9	40	4							
2JJSB 007 007 S04	0.35R X 0.7	0.7	40	4							
2JJSB 007 010 S04	0.35R X 0.7	1	40	4							
2JJSB 008 008 S04	0.4R X 0.8	0.8	40	4							
2JJSB 008 012 S04	0.4R X 0.8	1.2	40	4							
2JJSB 009 009 S04	0.45R X 0.9	0.9	40	4							
2JJSB 009 013 S04	0.45R X 0.9	1.3	40	4							
2JJSB 010 010 S04	0.5R X 1	1	40	4							
2JJSB 010 010 S06	0.5R X 1	1	40	6							
2JJSB 010 015 S04	0.5R X 1	1.5	40	4							
2JJSB 010 015 S06	0.5R X 1	1.5	40	6							
2JJSB 015 015 S04	0.75R X 1.5	1.5	40	4							
2JJSB 015 015 S06	0.75R X 1.5	1.5	40	6							
2JJSB 015 023 S04	0.75R X 1.5	2.3	40	4							
2JJSB 015 023 S06	0.75R X 1.5	2.3	40	6							
2JJSB 020 020 S04	1R X 2	2	45	4							
2JJSB 020 020 S06	1R X 2	2	45	6							
2JJSB 020 030 S04	1R X 2	3	45	4							
2JJSB 020 030 S06	1R X 2	3	45	6							
2JJSB 030 030 S04	1.5R X 3	3	45	4							
2JJSB 030 030 S06	1.5R X 3	3	45	6							
2JJSB 030 045 S04	1.5R X 3	4.5	45	4							
2JJSB 030 045 S06	1.5R X 3	4.5	45	6							
2JJSB 040 040 S04	2R X 4	4	45	4							
2JJSB 040 040 S06	2R X 4	4	45	6							
2JJSB 040 060 S04	2R X 4	6	45	4							
2JJSB 040 060 S06	2R X 4	6	45	6							
2JJSB 050 050 S06	2.5R X 5	5	50	6							
2JJSB 050 075 S06	2.5R X 5	7.5	50	6							
2JJSB 060 060 050	3R X 6	6	50	6							
2JJSB 060 080 055	3R X 6	8	55	6							
2JJSB 080 080 050	4R X 8	8	50	8							
2JJSB 080 110 060	4R X 8	11	60	8							
2JJSB 100 100 060	5R X 10	10	60	10							
2JJSB 100 130 060	5R X 10	13	60	10							



- 고경도강(HRc52~70), 프리하든강 계열의 고속가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 날부인선의 조도가 뛰어나 피삭재의 면조도가 우수합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRc52~70)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Very nice work surface finish.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.




0.05 ~ 2.5R 3 ~ 6R

D Size	D Tolerance
Ø0.1 ~ 0.15	+0 ~ -0.005mm
Ø0.2 ~ 5	+0 ~ -0.01mm
Ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm

Order Number	날경 Diameter R × D	날장 Length of cut L1	전장 Overall Length L	샙크 Dia d	비고						
2JJB 001 002 S04	0.05R X 0.1	0.2	40	4							
2JJB 0015 003 S04	0.075R X 0.15	0.3	40	4							
2JJB 002 004 S04	0.1R X 0.2	0.4	40	4							
2JJB 003 006 S04	0.15R X 0.3	0.6	40	4							
2JJB 004 008 S04	0.2R X 0.4	0.8	40	4							
2JJB 005 010 S04	0.25R X 0.5	1	45	4							
2JJB 006 012 S04	0.3R X 0.6	1.2	45	4							
2JJB 007 015 S04	0.35R X 0.7	1.5	45	4							
2JJB 008 020 S04	0.4R X 0.8	2	45	4							
2JJB 009 020 S04	0.45R X 0.9	2	45	4							
2JJB 010 025 S04	0.5R X 1	2.5	50	4							
2JJB 010 025 S06	0.5R X 1	2.5	50	6							
2JJB 010 025 070	0.5R X 1	2.5	70	6							
2JJB 012 030 S04	0.6R X 1.2	3	50	4							
2JJB 015 040 S04	0.75R X 1.5	4	50	4							
2JJB 015 040 S06	0.75R X 1.5	4	50	6							
2JJB 015 040 070	0.75R X 1.5	4	70	6							
2JJB 020 050 S04	1R X 2	5	50	4							
2JJB 020 050 S06	1R X 2	5	50	6							
2JJB 020 050 075	1R X 2	5	75	6							
2JJB 025 060 S04	1.25R X 2.5	6	50	4							
2JJB 025 060 S06	1.25R X 2.5	6	75	6							
2JJB 030 080 S04	1.5R X 3	8	50	4							
2JJB 030 080 S06	1.5R X 3	8	60	6							
2JJB 030 080 080	1.5R X 3	8	80	6							
2JJB 035 080 S06	1.75R X 3.5	8	60	6							
2JJB 040 080 S04	2R X 4	8	60	4							
2JJB 040 080 080	2R X 4	8	80	4							
2JJB 040 080 S06	2R X 4	8	70	6							
2JJB 040 080 090	2R X 4	8	90	6							
New 2JJB 045 080 S06	2.25R X 4.5	8	70	6							
2JJB 050 100 S06	2.5R X 5	10	75	6							
New 2JJB 055 100 S06	2.75R X 5.5	10	75	6							
2JJB 060 100 060	3R X 6	10	60	6							
New 2JJB 060 120 080	3R X 6	12	80	6							
2JJB 060 120 090	3R X 6	12	90	6							
New 2JJB 070 140 S08	3.5R X 7	14	80	8							
2JJB 080 120 060	4R X 8	12	60	8							
New 2JJB 080 140 090	4R X 8	14	90	8							
2JJB 080 140 100	4R X 8	14	100	8							
2JJB 100 150 070	5R X 10	15	70	10							
2JJB 100 180 100	5R X 10	18	100	10							
2JJB 120 180 075	6R X 12	18	75	12							
2JJB 120 220 110	6R X 12	22	110	12							



- 고경도강(HRC52~65), 프리하든강 계열의 고정밀가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 인선부 강성을 보강하여 날부치핑을 최소화 하였습니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRC52~65)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Reinforced edge design for preventing edge chipping.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.




D Size	D Tolerance
Ø0.1	+0 ~ -0.005mm
Ø0.2 ~ 5	+0 ~ -0.01mm
Ø6	-0.01 ~ -0.025mm

단위 : mm

Order Number	날경 Diameter D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샤프트 Shank Dia d	비고	Order Number	날경 Diameter D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샤프트 Shank Dia d	비고
2JJRE 001 003 S04	0.1	0.3	-	40	4		2JJRE 008 030 S04	0.8	0.8	3	40	4	
2JJRE 001 005 S04	0.1	0.5	-	40	4		2JJRE 008 040 S04	0.8	0.8	4	40	4	
2JJRE 002 005 S04	0.2	0.2	0.5	40	4		2JJRE 008 050 S04	0.8	0.8	5	40	4	
2JJRE 002 010 S04	0.2	0.2	1	40	4		2JJRE 008 060 S04	0.8	0.8	6	40	4	
2JJRE 002 015 S04	0.2	0.2	1.5	40	4		2JJRE 008 080 S04	0.8	0.8	8	45	4	
2JJRE 002 020 S04	0.2	0.2	2	40	4		2JJRE 008 100 S04	0.8	0.8	10	45	4	
2JJRE 002 025 S04	0.2	0.2	2.5	40	4		2JJRE 008 120 S04	0.8	0.8	12	45	4	
2JJRE 002 030 S04	0.2	0.2	3	40	4		2JJRE 009 040 S04	0.9	0.9	4	40	4	
2JJRE 003 010 S04	0.3	0.3	1	40	4		2JJRE 009 060 S04	0.9	0.9	6	40	4	
2JJRE 003 015 S04	0.3	0.3	1.5	40	4		2JJRE 009 080 S04	0.9	0.9	8	45	4	
2JJRE 003 020 S04	0.3	0.3	2	40	4		2JJRE 009 100 S04	0.9	0.9	10	45	4	
2JJRE 003 025 S04	0.3	0.3	2.5	40	4		2JJRE 010 020 S04	1	1	2	45	4	
2JJRE 003 030 S04	0.3	0.3	3	40	4		2JJRE 010 030 S04	1	1	3	45	4	
2JJRE 003 035 S04	0.3	0.3	3.5	40	4		2JJRE 010 040 S04	1	1	4	45	4	
2JJRE 003 040 S04	0.3	0.3	4	40	4		2JJRE 010 050 S04	1	1	5	45	4	
2JJRE 004 010 S04	0.4	0.4	1	40	4		2JJRE 010 060 S04	1	1	6	45	4	
2JJRE 004 015 S04	0.4	0.4	1.5	40	4		2JJRE 010 080 S04	1	1	8	45	4	
2JJRE 004 020 S04	0.4	0.4	2	40	4		2JJRE 010 100 S04	1	1	10	45	4	
2JJRE 004 025 S04	0.4	0.4	2.5	40	4		2JJRE 010 120 S04	1	1	12	50	4	
2JJRE 004 030 S04	0.4	0.4	3	40	4		2JJRE 010 140 S04	1	1	14	50	4	
2JJRE 004 035 S04	0.4	0.4	3.5	40	4		2JJRE 010 160 S04	1	1	16	50	4	
2JJRE 004 040 S04	0.4	0.4	4	40	4		2JJRE 010 180 S04	1	1	18	50	4	
2JJRE 004 050 S04	0.4	0.4	5	40	4		2JJRE 010 200 S04	1	1	20	50	4	
2JJRE 004 060 S04	0.4	0.4	6	40	4		2JJRE 010 220 S04	1	1	22	60	4	
2JJRE 004 080 S04	0.4	0.5	8	40	4		2JJRE 010 250 S04	1	1	25	60	4	
2JJRE 005 010 S04	0.5	0.5	1	40	4		2JJRE 012 040 S04	1.2	1.2	4	45	4	
2JJRE 005 020 S04	0.5	0.5	2	40	4		2JJRE 012 060 S04	1.2	1.2	6	45	4	
2JJRE 005 030 S04	0.5	0.5	3	40	4		2JJRE 012 080 S04	1.2	1.2	8	45	4	
2JJRE 005 040 S04	0.5	0.5	4	40	4		2JJRE 012 100 S04	1.2	1.2	10	45	4	
2JJRE 005 050 S04	0.5	0.5	5	40	4		2JJRE 012 120 S04	1.2	1.2	12	50	4	
2JJRE 005 060 S04	0.5	0.5	6	40	4		2JJRE 012 160 S04	1.2	1.2	16	50	4	
2JJRE 005 080 S04	0.5	0.5	8	45	4		2JJRE 012 200 S04	1.2	1.2	20	50	4	
2JJRE 005 100 S04	0.5	0.6	10	45	4		2JJRE 012 250 S04	1.2	1.2	25	60	4	
2JJRE 006 010 S04	0.6	0.6	1	40	4		2JJRE 014 080 S04	1.4	1.4	8	45	4	
2JJRE 006 020 S04	0.6	0.6	2	40	4		2JJRE 014 100 S04	1.4	1.4	10	45	4	
2JJRE 006 030 S04	0.6	0.6	3	40	4		2JJRE 014 140 S04	1.4	1.4	14	50	4	
2JJRE 006 040 S04	0.6	0.6	4	40	4		2JJRE 014 160 S04	1.4	1.4	16	50	4	
2JJRE 006 050 S04	0.6	0.6	5	40	4		2JJRE 014 200 S04	1.4	1.4	20	50	4	
2JJRE 006 060 S04	0.6	0.6	6	40	4		2JJRE 015 040 S04	1.5	1.5	4	45	4	
2JJRE 006 080 S04	0.6	0.6	8	45	4		2JJRE 015 060 S04	1.5	1.5	6	45	4	
2JJRE 006 100 S04	0.6	0.7	10	45	4		2JJRE 015 080 S04	1.5	1.5	8	45	4	
2JJRE 007 020 S04	0.7	0.7	2	40	4		2JJRE 015 100 S04	1.5	1.5	10	50	4	
2JJRE 007 040 S04	0.7	0.7	4	40	4		2JJRE 015 120 S04	1.5	1.5	12	50	4	
2JJRE 007 060 S04	0.7	0.7	6	40	4		2JJRE 015 140 S04	1.5	1.5	14	50	4	
2JJRE 007 080 S04	0.7	0.7	8	45	4		2JJRE 015 160 S04	1.5	1.5	16	50	4	
2JJRE 007 100 S04	0.7	0.7	10	45	4		2JJRE 015 180 S04	1.5	1.5	18	50	4	
2JJRE 008 010 S04	0.8	0.8	1	40	4		2JJRE 015 200 S04	1.5	1.5	20	50	4	
2JJRE 008 020 S04	0.8	0.8	2	40	4		2JJRE 015 220 S04	1.5	1.5	22	60	4	

단위 : mm

Order Number	날경 Diameter D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
2JJRE 015 250 S04	1.5	1.5	25	60	4		2JJRE 040 350 S06	4	4	35	75	6	
2JJRE 016 060 S04	1.6	1.6	6	45	4		2JJRE 040 400 S06	4	4	40	80	6	
2JJRE 016 100 S04	1.6	1.6	10	50	4		2JJRE 040 450 S06	4	4	45	90	6	
2JJRE 016 140 S04	1.6	1.6	14	50	4		2JJRE 040 500 S06	4	4	50	100	6	
2JJRE 016 180 S04	1.6	1.6	18	50	4		2JJRE 050 160 S06	5	6	16	60	6	
2JJRE 018 100 S04	1.8	1.8	10	50	4		2JJRE 050 200 S06	5	6	20	60	6	
2JJRE 018 140 S04	1.8	1.8	14	50	4		2JJRE 050 250 S06	5	6	25	65	6	
2JJRE 018 180 S04	1.8	1.8	18	50	4		2JJRE 050 300 S06	5	6	30	70	6	
2JJRE 020 060 S04	2	2	6	45	4		2JJRE 050 350 S06	5	6	35	75	6	
2JJRE 020 080 S04	2	2	8	45	4		2JJRE 050 400 S06	5	6	40	80	6	
2JJRE 020 100 S04	2	2	10	50	4		2JJRE 050 500 S06	5	6	50	100	6	
2JJRE 020 120 S04	2	2	12	50	4		2JJRE 060 200 S06	6	10	20	60	6	
2JJRE 020 140 S04	2	2	14	50	4		2JJRE 060 300 S06	6	10	30	75	6	
2JJRE 020 160 S04	2	2	16	50	4		2JJRE 060 400 S06	6	10	40	80	6	
2JJRE 020 180 S04	2	2	18	50	4		2JJRE 060 500 S06	6	10	50	90	6	
2JJRE 020 200 S04	2	2	20	50	4		2JJRE 060 600 S06	6	10	60	110	6	
2JJRE 020 220 S04	2	2	22	60	4								
2JJRE 020 250 S04	2	2	25	60	4								
2JJRE 020 300 S04	2	2	30	60	4								
2JJRE 020 350 S04	2	2	35	70	4								
2JJRE 020 400 S04	2	2	40	80	4								
2JJRE 025 100 S04	2.5	2.5	10	50	4								
2JJRE 025 120 S04	2.5	2.5	12	50	4								
2JJRE 025 160 S04	2.5	2.5	16	50	4								
2JJRE 025 200 S04	2.5	2.5	20	50	4								
2JJRE 025 250 S04	2.5	2.5	25	60	4								
2JJRE 025 300 S04	2.5	2.5	30	70	4								
2JJRE 025 350 S04	2.5	2.5	35	70	4								
2JJRE 025 400 S04	2.5	2.5	40	80	4								
2JJRE 030 060 S06	3	3	6	45	6								
2JJRE 030 080 S06	3	3	8	45	6								
2JJRE 030 100 S06	3	3	10	50	6								
2JJRE 030 120 S06	3	3	12	50	6								
2JJRE 030 160 S06	3	3	16	55	6								
2JJRE 030 200 S06	3	3	20	60	6								
2JJRE 030 250 S06	3	3	25	65	6								
2JJRE 030 300 S06	3	3	30	70	6								
2JJRE 030 350 S06	3	3	35	75	6								
2JJRE 030 400 S06	3	3	40	80	6								
2JJRE 030 450 S06	3	3	45	90	6								
2JJRE 030 500 S06	3	3	50	100	6								
2JJRE 040 080 S06	4	4	8	50	6								
2JJRE 040 100 S06	4	4	10	50	6								
2JJRE 040 120 S06	4	4	12	50	6								
2JJRE 040 160 S06	4	4	16	55	6								
2JJRE 040 200 S06	4	4	20	60	6								
2JJRE 040 250 S06	4	4	25	65	6								
2JJRE 040 300 S06	4	4	30	70	6								




- 고정도강(HRc52~65), 프리하든강 계열의 고정밀가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 인선부 강성을 보강하여 날부치핑을 최소화 하였습니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRc52~65)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Reinforced edge design for preventing edge chipping.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.

D Size	D Tolerance
$\phi 0.8 \sim 5$	+0 ~ -0.01mm
$\phi 6 \sim 12$	-0.01 ~ -0.025mm

단위 : mm

Order Number	날경 Diameter D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
4JJRE 008 010 S04	0.8	0.8	1	40	4		4JJRE 030 250 S06	3	3	25	65	6	
4JJRE 008 020 S04	0.8	0.8	2	40	4		4JJRE 030 300 S06	3	3	30	70	6	
4JJRE 008 030 S04	0.8	0.8	3	40	4		4JJRE 040 060 S06	4	4	6	50	6	
4JJRE 008 040 S04	0.8	0.8	4	40	4		4JJRE 040 080 S06	4	4	8	50	6	
4JJRE 008 050 S04	0.8	0.8	5	40	4		4JJRE 040 100 S06	4	4	10	50	6	
4JJRE 008 060 S04	0.8	0.8	6	40	4		4JJRE 040 120 S06	4	4	12	50	6	
4JJRE 008 080 S04	0.8	0.8	8	40	4		4JJRE 040 160 S06	4	4	16	55	6	
4JJRE 010 020 S04	1	1	2	45	4		4JJRE 040 200 S06	4	4	20	60	6	
4JJRE 010 030 S04	1	1	3	45	4		4JJRE 040 250 S06	4	4	25	65	6	
4JJRE 010 040 S04	1	1	4	45	4		4JJRE 040 300 S06	4	4	30	70	6	
4JJRE 010 060 S04	1	1	6	45	4		4JJRE 040 400 S06	4	4	40	80	6	
4JJRE 010 080 S04	1	1	8	45	4		4JJRE 050 160 S06	5	5	16	60	6	
4JJRE 010 100 S04	1	1	10	50	4		4JJRE 050 200 S06	5	5	20	60	6	
4JJRE 010 120 S04	1	1	12	50	4		4JJRE 050 250 S06	5	5	25	65	6	
4JJRE 010 140 S04	1	1	14	50	4		4JJRE 050 300 S06	5	5	30	70	6	
4JJRE 010 160 S04	1	1	16	50	4		4JJRE 050 400 S06	5	5	40	80	6	
4JJRE 012 040 S04	1.2	1.2	4	45	4		4JJRE 060 200 S06	6	6	20	60	6	
4JJRE 012 060 S04	1.2	1.2	6	45	4		4JJRE 060 300 S06	6	6	30	75	6	
4JJRE 012 080 S04	1.2	1.2	8	45	4		4JJRE 060 400 S06	6	6	40	80	6	
4JJRE 012 100 S04	1.2	1.2	10	50	4		4JJRE 060 500 S06	6	6	50	90	6	
4JJRE 012 120 S04	1.2	1.2	12	50	4		New 4JJRE 080 250 S08	8	12	25	65	8	
4JJRE 012 160 S04	1.2	1.2	16	50	4		New 4JJRE 080 400 S08	8	12	40	100	8	
4JJRE 015 040 S04	1.5	1.5	4	45	4		New 4JJRE 080 500 S08	8	12	50	110	8	
4JJRE 015 060 S04	1.5	1.5	6	45	4		New 4JJRE 100 300 S10	10	15	30	70	10	
4JJRE 015 080 S04	1.5	1.5	8	45	4		New 4JJRE 100 500 S10	10	15	50	100	10	
4JJRE 015 100 S04	1.5	1.5	10	50	4		New 4JJRE 100 600 S10	10	15	60	120	10	
4JJRE 015 120 S04	1.5	1.5	12	50	4		New 4JJRE 120 400 S12	12	18	40	80	12	
4JJRE 015 160 S04	1.5	1.5	16	50	4		New 4JJRE 120 600 S12	12	18	60	110	12	
4JJRE 020 040 S04	2	2	4	45	4		New 4JJRE 120 700 S12	12	18	70	130	12	
4JJRE 020 060 S04	2	2	6	45	4								
4JJRE 020 080 S04	2	2	8	45	4								
4JJRE 020 100 S04	2	2	10	50	4								
4JJRE 020 120 S04	2	2	12	50	4								
4JJRE 020 140 S04	2	2	14	50	4								
4JJRE 020 160 S04	2	2	16	50	4								
4JJRE 020 180 S04	2	2	18	50	4								
4JJRE 020 200 S04	2	2	20	50	4								
4JJRE 025 100 S04	2.5	2.5	10	50	4								
4JJRE 025 120 S04	2.5	2.5	12	50	4								
4JJRE 025 160 S04	2.5	2.5	16	50	4								
4JJRE 025 200 S04	2.5	2.5	20	50	4								
4JJRE 025 250 S04	2.5	2.5	25	60	4								
4JJRE 030 060 S06	3	3	6	45	6								
4JJRE 030 080 S06	3	3	8	45	6								
4JJRE 030 100 S06	3	3	10	50	6								
4JJRE 030 120 S06	3	3	12	50	6								
4JJRE 030 160 S06	3	3	16	55	6								
4JJRE 030 200 S06	3	3	20	60	6								



- 고정도강(HRc52~65), 프리하튼강 계열의 고속가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 인선부 강성을 보강하여 날부치핑을 최소화 하였습니다.
- 국내최초 날경 0.05mm 제품부터 생산합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRc52~65)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Reinforced edge design for preventing edge chipping.
- Produce down to 0.05mm in diameter endmills at the first time in Korea.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.




D Size	D Tolerance
$\phi 0.03 \sim 0.15$	+0 ~ -0.005mm
$\phi 0.2 \sim 5.5$	+0 ~ -0.01mm
$\phi 6 \sim 12$	-0.001 ~ -0.025mm
$\phi 14 \sim 20$	-0.015 ~ -0.03mm

단위 : mm

Order Number	날경 Diameter D	날장 Length of cut L1	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter D	날장 Length of cut L1	전장 Overall Length L	샙크 Shank Dia d	비고
New 2JJE 0003 00045 S04	0.03	0.045	40	4		2JJE 029 080 S04	2.9	8	45	4	
New 2JJE 0004 0006 S04	0.04	0.06	40	4		2JJE 030 080 S04	3	8	45	4	
2JJE 0005 0008 S04	0.05	0.08	40	4		2JJE 030 080 S06	3	8	45	6	
2JJE 0006 001 S04	0.06	0.1	40	4		2JJE 035 100 S06	3.5	10	45	6	
2JJE 0007 0012 S04	0.07	0.12	40	4		2JJE 040 100 S04	4	10	45	4	
2JJE 0008 0015 S04	0.08	0.15	40	4		2JJE 040 110 S06	4	11	45	6	
2JJE 0009 0017 S04	0.09	0.17	40	4		2JJE 045 110 S06	4.5	11	45	6	
2JJE 001 002 S04	0.1	0.2	40	4		2JJE 050 130 S06	5	13	50	6	
2JJE 0015 003 S04	0.15	0.3	40	4		2JJE 055 130 S06	5.5	13	50	6	
2JJE 002 004 S04	0.2	0.4	40	4		2JJE 060 130 S06	6	13	50	6	
2JJE 0025 005 S04	0.25	0.5	40	4		2JJE 065 160 S08	6.5	16	60	8	
2JJE 003 006 S04	0.3	0.6	40	4		2JJE 070 160 S08	7	16	60	8	
2JJE 0035 007 S04	0.35	0.7	40	4		2JJE 075 160 S08	7.5	16	60	8	
2JJE 004 008 S04	0.4	0.8	40	4		2JJE 080 190 S08	8	19	60	8	
2JJE 0045 009 S04	0.45	0.9	40	4		2JJE 085 190 S10	8.5	19	70	10	
2JJE 005 010 S04	0.5	1	40	4		2JJE 090 190 S10	9	19	70	10	
2JJE 0055 011 S04	0.55	1.1	40	4		2JJE 095 190 S10	9.5	19	70	10	
2JJE 006 012 S04	0.6	1.2	40	4		2JJE 100 220 S10	10	22	70	10	
2JJE 0065 013 S04	0.65	1.3	40	4		2JJE 105 220 S12	10.5	22	75	12	
2JJE 007 014 S04	0.7	1.4	40	4		2JJE 110 220 S12	11	22	75	12	
2JJE 0075 015 S04	0.75	1.5	40	4		2JJE 115 220 S12	11.5	22	75	12	
2JJE 008 016 S04	0.8	1.6	40	4		2JJE 120 260 S12	12	26	75	12	
2JJE 0085 017 S04	0.85	1.7	40	4		2JJE 140 260 S14	14	26	80	14	
2JJE 009 020 S04	0.9	2	40	4		2JJE 140 260 S16	14	26	90	16	
2JJE 0095 020 S04	0.95	2	40	4		2JJE 160 350 S16	16	35	100	16	
2JJE 010 025 S04	1	2.5	40	4		2JJE 180 350 S18	18	35	100	18	
2JJE 010 025 S06	1	2.5	40	6		2JJE 200 400 S20	20	40	100	20	
2JJE 011 027 S04	1.1	2.7	40	4							
2JJE 012 030 S04	1.2	3	40	4							
2JJE 013 032 S04	1.3	3.2	40	4							
2JJE 014 035 S04	1.4	3.5	40	4							
2JJE 015 040 S04	1.5	4	40	4							
2JJE 015 040 S06	1.5	4	40	6							
2JJE 016 040 S04	1.6	4	40	4							
2JJE 017 042 S04	1.7	4.2	40	4							
2JJE 018 045 S04	1.8	4.5	40	4							
2JJE 019 050 S04	1.9	5	40	4							
2JJE 020 060 S04	2	6	40	4							
2JJE 020 060 S06	2	6	40	6							
2JJE 021 060 S04	2.1	6	40	4							
2JJE 022 060 S04	2.2	6	40	4							
2JJE 023 060 S04	2.3	6	40	4							
2JJE 024 080 S04	2.4	8	45	4							
2JJE 025 080 S04	2.5	8	45	4							
2JJE 025 080 S06	2.5	8	45	6							
2JJE 026 080 S04	2.6	8	45	4							
2JJE 027 080 S04	2.7	8	45	4							
2JJE 028 080 S04	2.8	8	45	4							

4날 고경도재 가공용 제이제이 엔드밀



- **고경도강(HRc52~65), 프리하드강 계열의 고속가공 엔드밀**
- 고풍량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 인선부 강성을 보강하여 날부치핑을 최소화 하였습니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- **Endmills for pre-hardened and hardened steel (HRc52~65)**
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Reinforced edge design for preventing edge chipping.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.



Ø0.5 ~ 5.5

Ø6 ~ 12


Ø14 ~ 20

Shield Edge


D Size	D Tolerance
∅0.5 ~ 5.5	+0 ~ -0.01mm
∅6 ~ 12	-0.01 ~ -0.025mm
∅14 ~ 20	-0.015 ~ -0.03mm

단위 : mm

[illegible]



- **고경도강(HRC52~65), 프리하든강 계열의 고속가공 엔드밀**
- 고탄량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 인선부 강성을 보강하여 날부치핑을 최소화 하였습니다.
- 45° 헬릭스 형상으로 설계하여 고속, 고이송 가공에 적합합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- **Endmills for pre-hardened and hardened steel (HRC52~65)**
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Reinforced edge design for preventing edge chipping.
- 45° degree helix design for high speed, feed condition.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.



01 ~ 5

Ø6 ~ 12

Ø16 ~ 20


Shield Edge

D Size	D Tolerance
Ø1 ~ 5	+0 ~ -0.01mm
Ø6 ~ 12	-0.01 ~ -0.025mm
Ø16 ~ 20	-0.015 ~ -0.03mm

단위 : mm

Order Number	날경 Diameter D	날장 Length of cut L1	전장 Overall Length L	샙크 Shank Dia d	비고
4JJHE 010 015 S06	1	1.5	40	6	
4JJHE 010 025 S06	1	2.5	40	6	
4JJHE 010 035 S06	1	3.5	40	6	
New 4JJHE 010 050 S06	1	5	45	6	
New 4JJHE 015 040 S06	1.5	4	40	6	
New 4JJHE 015 060 S06	1.5	6	40	6	
New 4JJHE 015 080 S06	1.5	8	40	6	
4JJHE 020 030 S06	2	3	40	6	
4JJHE 020 050 S06	2	5	40	6	
4JJHE 020 080 S06	2	8	40	6	
New 4JJHE 020 100 S06	2	10	45	6	
4JJHE 025 060 S06	2.5	6	45	6	
4JJHE 025 080 S06	2.5	8	45	6	
New 4JJHE 025 100 S06	2.5	10	50	6	
4JJHE 030 060 S06	3	6	45	6	
4JJHE 030 080 S06	3	8	45	6	
4JJHE 030 120 S06	3	12	50	6	
New 4JJHE 030 150 S06	3	15	50	6	
New 4JJHE 035 080 S06	3.5	8	45	6	
4JJHE 040 080 S06	4	8	45	6	
4JJHE 040 110 S06	4	11	45	6	
4JJHE 040 150 S06	4	15	55	6	
New 4JJHE 040 200 S06	4	20	60	6	
New 4JJHE 045 110 S06	4.5	11	50	6	
4JJHE 050 100 S06	5	10	50	6	
4JJHE 050 130 S06	5	13	50	6	
4JJHE 050 200 S06	5	20	60	6	
New 4JJHE 050 250 S06	5	25	70	6	
New 4JJHE 050 300 S06	5	30	75	6	
4JJHE 060 130 S06	6	13	50	6	
4JJHE 060 150 S06	6	15	55	6	
4JJHE 060 200 S06	6	20	60	6	
New 4JJHE 060 250 S06	6	25	70	6	
New 4JJHE 060 300 S06	6	30	75	6	
New 4JJHE 070 160 S08	7	16	60	8	
4JJHE 080 200 S08	8	20	60	8	
4JJHE 080 250 S08	8	25	70	8	
New 4JJHE 080 300 S08	8	30	80	8	
New 4JJHE 080 400 S08	8	40	90	8	
New 4JJHE 090 220 S10	9	22	70	10	
4JJHE 100 220 S10	10	22	70	10	
4JJHE 100 300 S10	10	30	80	10	
New 4JJHE 100 400 S10	10	40	90	10	
New 4JJHE 100 500 S10	10	50	100	10	
4JJHE 120 260 S12	12	26	75	12	
4JJHE 120 350 S12	12	35	90	12	
New 4JJHE 120 500 S12	12	50	100	12	
New 4JJHE 120 600 S12	12	60	110	12	

6&8날 고경도재 가공용 제이제이45° 헬릭스 엔드밀



- 고경도강(HRc52~70), 프리하든강 계열의 고속가공 엔드밀
- 고품질 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 균일한 런아웃과 고정밀 공차 적용으로 초정밀가공에 적합합니다.
- 인선부 강성을 보강하여 날부치핑을 최소화 하였습니다.
- 45°헬릭스 형상으로 설계하여 고속,고이송 가공에 적합합니다.
- 초미립자 초경합금(0.2μm)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRc52~70)
- Good wear resistance by high quality Si-based PVD coating.
- Precise run-out and tolerance for finish machining.
- Reinforced edge design for preventing edge chipping.
- 45°degree helix design for high speed, feed condition.
- Outstanding performance at high speed machining by ultra fine (0.2μm) WC grade.




D Size	D Tolerance
Ø3 ~ 5	+0 ~ -0.01mm
Ø6 ~ 12	-0.01 ~ -0.025mm
Ø14 ~ 20	-0.015 ~ -0.03mm

단위 : mm

Order Number	날경 Diameter D	날장 Length of cut L1	전장 Overall Length L	샅크 Shank Dia d	비고	Order Number	날경 Diameter D	날장 Length of cut L1	전장 Overall Length L	샅크 Shank Dia d	비고
6JJHE 030 100 S06	3	10	50	6		6JJHE 200 1200 S20	20	120	180	20	
6JJHE 030 150 S06	3	15	50	6		8JJHE 250 1000 S25	25	100	160	25	
New 6JJHE 030 200 S06	3	20	60	6		8JJHE 250 1300 S25	25	130	200	25	
6JJHE 040 120 S06	4	12	50	6							
6JJHE 040 160 S06	4	16	50	6							
New 6JJHE 040 200 S06	4	20	60	6							
6JJHE 050 150 S06	5	15	50	6							
6JJHE 050 200 S06	5	20	60	6							
New 6JJHE 050 250 S06	5	25	60	6							
6JJHE 060 150 S06	6	15	50	6							
6JJHE 060 200 S06	6	20	60	6							
6JJHE 060 250 S06	6	25	65	6							
6JJHE 060 300 S06	6	30	70	6							
6JJHE 060 350 S06	6	35	75	6							
New 6JJHE 060 400 S06	6	40	80	6							
6JJHE 080 200 S08	8	20	60	8							
6JJHE 080 250 S08	8	25	65	8							
6JJHE 080 300 S08	8	30	75	8							
6JJHE 080 350 S08	8	35	80	8							
6JJHE 080 400 S08	8	40	90	8							
6JJHE 080 450 S08	8	45	100	8							
6JJHE 080 500 S08	8	50	100	8							
6JJHE 100 250 S10	10	25	70	10							
6JJHE 100 350 S10	10	35	90	10							
6JJHE 100 450 S10	10	45	100	10							
6JJHE 100 500 S10	10	50	100	10							
6JJHE 100 600 S10	10	60	110	10							
6JJHE 120 300 S12	12	30	80	12							
6JJHE 120 400 S12	12	40	90	12							
6JJHE 120 500 S12	12	50	100	12							
6JJHE 120 600 S12	12	60	110	12							
6JJHE 120 700 S12	12	70	120	12							
New 6JJHE 140 350 S14	14	35	90	14							
New 6JJHE 140 550 S14	14	55	110	14							
6JJHE 160 350 S16	16	35	90	16							
6JJHE 160 500 S16	16	50	110	16							
6JJHE 160 650 S16	16	65	120	16							
6JJHE 160 800 S16	16	80	150	16							
6JJHE 160 900 S16	16	90	160	16							
6JJHE 160 1000 S16	16	100	160	16							
New 6JJHE 180 400 S18	18	40	100	18							
New 6JJHE 180 650 S18	18	65	120	18							
6JJHE 200 450 S20	20	45	100	20							
6JJHE 200 600 S20	20	60	120	20							
6JJHE 200 800 S20	20	80	150	20							
6JJHE 200 900 S20	20	90	160	20							
6JJHE 200 1000 S20	20	100	160	20							
6JJHE 200 1100 S20	20	110	170	20							

2날 고정도재 가공용 제이제이 리브 코너 레디우스 엔드밀

JJ series



R0.02 ~ 0.5 R1 ~ 1.5 R2 ~ 3

- 고정도강(HRC52~70), 프리하든강 계열의 고정밀가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 코너R 형상을 날부치핑이 적도록 설계하였습니다.
- 다양한 코너R과 유효장으로 맞춤 가공이 가능합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- **Endmills for pre-hardened and hardened steel(HRC52~70)**
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Designed for minimizing edge chipping by corner R shape.
- Various corner R and flute length for wide range application.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.

D Size	D Tolerance
$\phi 0.2 \sim 5$	+0 ~ -0.01mm
$\phi 6 \sim 12$	-0.005 ~ -0.015mm
$\phi 16$	-0.01 ~ -0.02mm

단위 : mm

Order Number	날경 Diameter D x R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샤프트 Shank Dia d	비고
2JJCR 002 0002 005	0.2 X R0.02	0.2	0.5	40	4	
2JJCR 002 0002 010	0.2 X R0.02	0.2	1	40	4	
2JJCR 002 0002 015	0.2 X R0.02	0.2	1.5	40	4	
2JJCR 002 0005 005	0.2 X R0.05	0.2	0.5	40	4	
2JJCR 002 0005 010	0.2 X R0.05	0.2	1	40	4	
2JJCR 002 0005 015	0.2 X R0.05	0.2	1.5	40	4	
2JJCR 003 0002 010	0.3 X R0.02	0.3	1	40	4	
2JJCR 003 0002 020	0.3 X R0.02	0.3	2	40	4	
2JJCR 003 0002 030	0.3 X R0.02	0.3	3	40	4	
2JJCR 003 0005 010	0.3 X R0.05	0.3	1	40	4	
2JJCR 003 0005 020	0.3 X R0.05	0.3	2	40	4	
2JJCR 003 0005 030	0.3 X R0.05	0.3	3	40	4	
2JJCR 004 0002 010	0.4 X R0.02	0.4	1	40	4	
2JJCR 004 0002 020	0.4 X R0.02	0.4	2	40	4	
2JJCR 004 0002 030	0.4 X R0.02	0.4	3	40	4	
2JJCR 004 0002 040	0.4 X R0.02	0.4	4	40	4	
2JJCR 004 0005 010	0.4 X R0.05	0.4	1	40	4	
2JJCR 004 0005 020	0.4 X R0.05	0.4	2	40	4	
2JJCR 004 0005 030	0.4 X R0.05	0.4	3	40	4	
2JJCR 004 0005 040	0.4 X R0.05	0.4	4	40	4	
2JJCR 004 001 010	0.4 X R0.1	0.4	1	40	4	
2JJCR 004 001 015	0.4 X R0.1	0.4	1.5	40	4	
2JJCR 004 001 020	0.4 X R0.1	0.4	2	40	4	
2JJCR 004 001 030	0.4 X R0.1	0.4	3	40	4	
2JJCR 004 001 040	0.4 X R0.1	0.4	4	40	4	
2JJCR 005 0002 010	0.5 X R0.02	0.5	1	45	4	
2JJCR 005 0002 015	0.5 X R0.02	0.5	1.5	45	4	
2JJCR 005 0002 020	0.5 X R0.02	0.5	2	45	4	
2JJCR 005 0002 025	0.5 X R0.02	0.5	2.5	45	4	
2JJCR 005 0002 030	0.5 X R0.02	0.5	3	45	4	
2JJCR 005 0002 040	0.5 X R0.02	0.5	4	45	4	
2JJCR 005 0002 050	0.5 X R0.02	0.5	5	45	4	
2JJCR 005 0002 060	0.5 X R0.02	0.5	6	45	4	
2JJCR 005 0005 010	0.5 X R0.05	0.5	1	45	4	
2JJCR 005 0005 015	0.5 X R0.05	0.5	1.5	45	4	
2JJCR 005 0005 020	0.5 X R0.05	0.5	2	45	4	
2JJCR 005 0005 025	0.5 X R0.05	0.5	2.5	45	4	
2JJCR 005 0005 030	0.5 X R0.05	0.5	3	45	4	
2JJCR 005 0005 040	0.5 X R0.05	0.5	4	45	4	
2JJCR 005 0005 050	0.5 X R0.05	0.5	5	45	4	
2JJCR 005 0005 060	0.5 X R0.05	0.5	6	45	4	
2JJCR 005 001 010	0.5 X R0.1	0.5	1	45	4	
2JJCR 005 001 015	0.5 X R0.1	0.5	1.5	45	4	
2JJCR 005 001 020	0.5 X R0.1	0.5	2	45	4	
2JJCR 005 001 025	0.5 X R0.1	0.5	2.5	45	4	
2JJCR 005 001 030	0.5 X R0.1	0.5	3	45	4	
2JJCR 005 001 040	0.5 X R0.1	0.5	4	45	4	
2JJCR 005 001 050	0.5 X R0.1	0.5	5	45	4	

Order Number	날경 Diameter D x R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샤프트 Shank Dia d	비고
2JJCR 005 001 060	0.5 X R0.1	0.5	6	45	4	
2JJCR 006 0002 020	0.6 X R0.02	0.6	2	45	4	
2JJCR 006 0002 030	0.6 X R0.02	0.6	3	45	4	
2JJCR 006 0002 040	0.6 X R0.02	0.6	4	45	4	
2JJCR 006 0002 060	0.6 X R0.02	0.6	6	45	4	
2JJCR 006 0002 080	0.6 X R0.02	0.6	8	45	4	
New 2JJCR 006 0002 100	0.6 X R0.02	0.6	10	45	4	
2JJCR 006 0005 020	0.6 X R0.05	0.6	2	45	4	
2JJCR 006 0005 030	0.6 X R0.05	0.6	3	45	4	
2JJCR 006 0005 040	0.6 X R0.05	0.6	4	45	4	
2JJCR 006 0005 060	0.6 X R0.05	0.6	6	45	4	
2JJCR 006 0005 080	0.6 X R0.05	0.6	8	45	4	
New 2JJCR 006 0005 100	0.6 X R0.05	0.6	10	45	4	
2JJCR 006 001 020	0.6 X R0.1	0.6	2	45	4	
2JJCR 006 001 030	0.6 X R0.1	0.6	3	45	4	
2JJCR 006 001 040	0.6 X R0.1	0.6	4	45	4	
2JJCR 006 001 060	0.6 X R0.1	0.6	6	45	4	
2JJCR 006 001 080	0.6 X R0.1	0.6	8	45	4	
New 2JJCR 006 001 100	0.6 X R0.1	0.6	10	45	4	
2JJCR 007 001 020	0.7 X R0.1	0.7	2	45	4	
2JJCR 007 001 040	0.7 X R0.1	0.7	4	45	4	
2JJCR 007 001 060	0.7 X R0.1	0.7	6	45	4	
2JJCR 008 0002 020	0.8 X R0.02	0.8	2	45	4	
2JJCR 008 0002 040	0.8 X R0.02	0.8	4	45	4	
2JJCR 008 0002 060	0.8 X R0.02	0.8	6	45	4	
2JJCR 008 0002 080	0.8 X R0.02	0.8	8	45	4	
New 2JJCR 008 0002 100	0.8 X R0.02	0.8	10	45	4	
2JJCR 008 0005 020	0.8 X R0.05	0.8	2	45	4	
2JJCR 008 0005 040	0.8 X R0.05	0.8	4	45	4	
2JJCR 008 0005 060	0.8 X R0.05	0.8	6	45	4	
2JJCR 008 0005 080	0.8 X R0.05	0.8	8	45	4	
New 2JJCR 008 0005 100	0.8 X R0.05	0.8	10	45	4	
2JJCR 008 001 020	0.8 X R0.1	0.8	2	45	4	
2JJCR 008 001 040	0.8 X R0.1	0.8	4	45	4	
2JJCR 008 001 060	0.8 X R0.1	0.8	6	45	4	
2JJCR 008 001 080	0.8 X R0.1	0.8	8	45	4	
New 2JJCR 008 001 100	0.8 X R0.1	0.8	10	45	4	
2JJCR 008 002 020	0.8 X R0.2	0.8	2	45	4	
2JJCR 008 002 040	0.8 X R0.2	0.8	4	45	4	
2JJCR 008 002 060	0.8 X R0.2	0.8	6	45	4	
2JJCR 008 002 080	0.8 X R0.2	0.8	8	45	4	
New 2JJCR 008 002 100	0.8 X R0.2	0.8	10	45	4	
2JJCR 010 0002 040	1 X R0.02	1	4	45	4	
2JJCR 010 0002 060	1 X R0.02	1	6	45	4	
2JJCR 010 0002 080	1 X R0.02	1	8	45	4	
2JJCR 010 0002 100	1 X R0.02	1	10	50	4	
2JJCR 010 0002 120	1 X R0.02	1	12	50	4	
2JJCR 010 0002 160	1 X R0.02	1	16	50	4	

단위 : mm

Order Number	날경 D × R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 D × R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
2JJCR 010 0002 200	1 X R0.02	1	20	50	4		2JJCR 012 003 200	1.2 X R0.3	1.2	20	50	4	
2JJCR 010 0005 040	1 X R0.05	1	4	45	4		2JJCR 015 0002 040	1.5 X R0.02	1.5	4	45	4	
2JJCR 010 0005 060	1 X R0.05	1	6	45	4		2JJCR 015 0002 060	1.5 X R0.02	1.5	6	45	4	
2JJCR 010 0005 080	1 X R0.05	1	8	45	4		2JJCR 015 0002 080	1.5 X R0.02	1.5	8	45	4	
2JJCR 010 0005 100	1 X R0.05	1	10	50	4		2JJCR 015 0002 100	1.5 X R0.02	1.5	10	50	4	
2JJCR 010 0005 120	1 X R0.05	1	12	50	4		2JJCR 015 0002 120	1.5 X R0.02	1.5	12	50	4	
2JJCR 010 0005 160	1 X R0.05	1	16	50	4		2JJCR 015 0002 160	1.5 X R0.02	1.5	16	50	4	
2JJCR 010 0005 200	1 X R0.05	1	20	50	4		2JJCR 015 0002 200	1.5 X R0.02	1.5	20	50	4	
2JJCR 010 001 040	1 X R0.1	1	4	45	4		2JJCR 015 0005 040	1.5 X R0.05	1.5	4	45	4	
2JJCR 010 001 060	1 X R0.1	1	6	45	4		2JJCR 015 0005 060	1.5 X R0.05	1.5	6	45	4	
2JJCR 010 001 080	1 X R0.1	1	8	45	4		2JJCR 015 0005 080	1.5 X R0.05	1.5	8	45	4	
2JJCR 010 001 100	1 X R0.1	1	10	50	4		2JJCR 015 0005 100	1.5 X R0.05	1.5	10	50	4	
2JJCR 010 001 120	1 X R0.1	1	12	50	4		2JJCR 015 0005 120	1.5 X R0.05	1.5	12	50	4	
2JJCR 010 001 160	1 X R0.1	1	16	50	4		2JJCR 015 0005 160	1.5 X R0.05	1.5	16	50	4	
2JJCR 010 001 200	1 X R0.1	1	20	50	4		2JJCR 015 0005 200	1.5 X R0.05	1.5	20	50	4	
2JJCR 010 002 040	1 X R0.2	1	4	45	4		2JJCR 015 001 040	1.5 X R0.1	1.5	4	45	4	
2JJCR 010 002 060	1 X R0.2	1	6	45	4		2JJCR 015 001 060	1.5 X R0.1	1.5	6	45	4	
2JJCR 010 002 080	1 X R0.2	1	8	45	4		2JJCR 015 001 080	1.5 X R0.1	1.5	8	45	4	
2JJCR 010 002 100	1 X R0.2	1	10	50	4		2JJCR 015 001 100	1.5 X R0.1	1.5	10	50	4	
2JJCR 010 002 120	1 X R0.2	1	12	50	4		2JJCR 015 001 120	1.5 X R0.1	1.5	12	50	4	
2JJCR 010 002 160	1 X R0.2	1	16	50	4		2JJCR 015 001 160	1.5 X R0.1	1.5	16	50	4	
2JJCR 010 002 200	1 X R0.2	1	20	50	4		2JJCR 015 001 200	1.5 X R0.1	1.5	20	50	4	
2JJCR 010 003 040	1 X R0.3	1	4	45	4		2JJCR 015 002 040	1.5 X R0.2	1.5	4	45	4	
2JJCR 010 003 060	1 X R0.3	1	6	45	4		2JJCR 015 002 060	1.5 X R0.2	1.5	6	45	4	
2JJCR 010 003 080	1 X R0.3	1	8	45	4		2JJCR 015 002 080	1.5 X R0.2	1.5	8	45	4	
2JJCR 010 003 100	1 X R0.3	1	10	50	4		2JJCR 015 002 100	1.5 X R0.2	1.5	10	50	4	
2JJCR 010 003 120	1 X R0.3	1	12	50	4		2JJCR 015 002 120	1.5 X R0.2	1.5	12	50	4	
2JJCR 010 003 160	1 X R0.3	1	16	50	4		2JJCR 015 002 160	1.5 X R0.2	1.5	16	50	4	
2JJCR 010 003 200	1 X R0.3	1	20	50	4		2JJCR 015 002 200	1.5 X R0.2	1.5	20	50	4	
2JJCR 012 0002 040	1.2 X R0.02	1.2	4	45	4		2JJCR 015 003 040	1.5 X R0.3	1.5	4	45	4	
2JJCR 012 0002 060	1.2 X R0.02	1.2	6	45	4		2JJCR 015 003 060	1.5 X R0.3	1.5	6	45	4	
2JJCR 012 0002 080	1.2 X R0.02	1.2	8	45	4		2JJCR 015 003 080	1.5 X R0.3	1.5	8	45	4	
2JJCR 012 0002 100	1.2 X R0.02	1.2	10	50	4		2JJCR 015 003 100	1.5 X R0.3	1.5	10	50	4	
2JJCR 012 0002 120	1.2 X R0.02	1.2	12	50	4		2JJCR 015 003 120	1.5 X R0.3	1.5	12	50	4	
2JJCR 012 0002 160	1.2 X R0.02	1.2	16	50	4		2JJCR 015 003 160	1.5 X R0.3	1.5	16	50	4	
2JJCR 012 0002 200	1.2 X R0.02	1.2	20	50	4		2JJCR 015 003 200	1.5 X R0.3	1.5	20	50	4	
2JJCR 012 0005 040	1.2 X R0.05	1.2	4	45	4		2JJCR 015 005 040	1.5 X R0.5	1.5	4	45	4	
2JJCR 012 0005 060	1.2 X R0.05	1.2	6	45	4		2JJCR 015 005 060	1.5 X R0.5	1.5	6	45	4	
2JJCR 012 0005 080	1.2 X R0.05	1.2	8	45	4		2JJCR 015 005 080	1.5 X R0.5	1.5	8	45	4	
2JJCR 012 0005 100	1.2 X R0.05	1.2	10	50	4		2JJCR 015 005 100	1.5 X R0.5	1.5	10	50	4	
2JJCR 012 0005 120	1.2 X R0.05	1.2	12	50	4		2JJCR 015 005 120	1.5 X R0.5	1.5	12	50	4	
2JJCR 012 0005 160	1.2 X R0.05	1.2	16	50	4		2JJCR 015 005 160	1.5 X R0.5	1.5	16	50	4	
2JJCR 012 0005 200	1.2 X R0.05	1.2	20	50	4		2JJCR 015 005 200	1.5 X R0.5	1.5	20	50	4	
2JJCR 012 001 040	1.2 X R0.1	1.2	4	45	4		2JJCR 020 0002 060	2 X R0.02	2	6	45	4	
2JJCR 012 001 060	1.2 X R0.1	1.2	6	45	4		2JJCR 020 0002 080	2 X R0.02	2	8	45	4	
2JJCR 012 001 080	1.2 X R0.1	1.2	8	45	4		2JJCR 020 0002 100	2 X R0.02	2	10	50	4	
2JJCR 012 001 100	1.2 X R0.1	1.2	10	50	4		2JJCR 020 0002 120	2 X R0.02	2	12	50	4	
2JJCR 012 001 120	1.2 X R0.1	1.2	12	50	4		2JJCR 020 0002 160	2 X R0.02	2	16	50	4	
2JJCR 012 001 160	1.2 X R0.1	1.2	16	50	4		2JJCR 020 0002 200	2 X R0.02	2	20	50	4	
2JJCR 012 001 200	1.2 X R0.1	1.2	20	50	4		2JJCR 020 0002 250	2 X R0.02	2	25	60	4	
2JJCR 012 002 040	1.2 X R0.2	1.2	4	45	4		2JJCR 020 0005 060	2 X R0.05	2	6	45	4	
2JJCR 012 002 060	1.2 X R0.2	1.2	6	45	4		2JJCR 020 0005 080	2 X R0.05	2	8	45	4	
2JJCR 012 002 080	1.2 X R0.2	1.2	8	45	4		2JJCR 020 0005 100	2 X R0.05	2	10	50	4	
2JJCR 012 002 100	1.2 X R0.2	1.2	10	50	4		2JJCR 020 0005 120	2 X R0.05	2	12	50	4	
2JJCR 012 002 120	1.2 X R0.2	1.2	12	50	4		2JJCR 020 0005 160	2 X R0.05	2	16	50	4	
2JJCR 012 002 160	1.2 X R0.2	1.2	16	50	4		2JJCR 020 0005 200	2 X R0.05	2	20	50	4	
2JJCR 012 002 200	1.2 X R0.2	1.2	20	50	4		2JJCR 020 0005 250	2 X R0.05	2	25	60	4	
2JJCR 012 003 040	1.2 X R0.3	1.2	4	45	4		2JJCR 020 001 060	2 X R0.1	2	6	45	4	
2JJCR 012 003 060	1.2 X R0.3	1.2	6	45	4		2JJCR 020 001 080	2 X R0.1	2	8	45	4	
2JJCR 012 003 080	1.2 X R0.3	1.2	8	45	4		2JJCR 020 001 100	2 X R0.1	2	10	50	4	
2JJCR 012 003 100	1.2 X R0.3	1.2	10	50	4		2JJCR 020 001 120	2 X R0.1	2	12	50	4	
2JJCR 012 003 120	1.2 X R0.3	1.2	12	50	4		2JJCR 020 001 160	2 X R0.1	2	16	50	4	
2JJCR 012 003 160	1.2 X R0.3	1.2	16	50	4		2JJCR 020 001 200	2 X R0.1	2	20	50	4	

단위 : mm


Order Number	날경 Diameter D×R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter D×R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
2JJCR 020 001 250	2 X R0.1	2	25	60	4		2JJCR 030 003 400	3 X R0.3	3	40	80	6	
New 2JJCR 020 001 300	2 X R0.1	2	30	70	4		2JJCR 030 005 100	3 X R0.5	3	10	50	6	
2JJCR 020 002 060	2 X R0.2	2	6	45	4		2JJCR 030 005 120	3 X R0.5	3	12	50	6	
2JJCR 020 002 080	2 X R0.2	2	8	45	4		2JJCR 030 005 160	3 X R0.5	3	16	55	6	
2JJCR 020 002 100	2 X R0.2	2	10	50	4		2JJCR 030 005 200	3 X R0.5	3	20	60	6	
2JJCR 020 002 120	2 X R0.2	2	12	50	4		2JJCR 030 005 250	3 X R0.5	3	25	65	6	
2JJCR 020 002 160	2 X R0.2	2	16	50	4		2JJCR 030 005 300	3 X R0.5	3	30	70	6	
2JJCR 020 002 200	2 X R0.2	2	20	50	4		2JJCR 030 005 350	3 X R0.5	3	35	75	6	
2JJCR 020 002 250	2 X R0.2	2	25	60	4		2JJCR 030 005 400	3 X R0.5	3	40	80	6	
New 2JJCR 020 002 300	2 X R0.2	2	30	70	4		2JJCR 030 010 100	3 X R1	3	10	50	6	
2JJCR 020 003 060	2 X R0.3	2	6	45	4		2JJCR 030 010 120	3 X R1	3	12	50	6	
2JJCR 020 003 080	2 X R0.3	2	8	45	4		2JJCR 030 010 160	3 X R1	3	16	55	6	
2JJCR 020 003 100	2 X R0.3	2	10	50	4		2JJCR 030 010 200	3 X R1	3	20	60	6	
2JJCR 020 003 120	2 X R0.3	2	12	50	4		2JJCR 030 010 250	3 X R1	3	25	65	6	
2JJCR 020 003 160	2 X R0.3	2	16	50	4		2JJCR 030 010 300	3 X R1	3	30	70	6	
2JJCR 020 003 200	2 X R0.3	2	20	50	4		2JJCR 030 010 350	3 X R1	3	35	75	6	
2JJCR 020 003 250	2 X R0.3	2	25	60	4		2JJCR 030 010 400	3 X R1	3	40	80	6	
New 2JJCR 020 003 300	2 X R0.3	2	30	70	4		2JJCR 040 001 120	4 X R0.1	4	12	50	6	
2JJCR 020 005 060	2 X R0.5	2	6	45	4		2JJCR 040 001 160	4 X R0.1	4	16	55	6	
2JJCR 020 005 080	2 X R0.5	2	8	45	4		2JJCR 040 001 200	4 X R0.1	4	20	60	6	
2JJCR 020 005 100	2 X R0.5	2	10	50	4		2JJCR 040 001 250	4 X R0.1	4	25	65	6	
2JJCR 020 005 120	2 X R0.5	2	12	50	4		2JJCR 040 001 300	4 X R0.1	4	30	70	6	
2JJCR 020 005 160	2 X R0.5	2	16	50	4		2JJCR 040 001 350	4 X R0.1	4	35	75	6	
2JJCR 020 005 200	2 X R0.5	2	20	50	4		2JJCR 040 001 400	4 X R0.1	4	40	80	6	
2JJCR 020 005 250	2 X R0.5	2	25	60	4		2JJCR 040 002 120	4 X R0.2	4	12	50	6	
New 2JJCR 020 005 300	2 X R0.5	2	30	70	4		2JJCR 040 002 160	4 X R0.2	4	16	55	6	
2JJCR 025 001 100	2.5 X R0.1	2.5	10	50	4		2JJCR 040 002 200	4 X R0.2	4	20	60	6	
2JJCR 025 001 160	2.5 X R0.1	2.5	16	50	4		2JJCR 040 002 250	4 X R0.2	4	25	65	6	
2JJCR 025 001 200	2.5 X R0.1	2.5	20	50	4		2JJCR 040 002 300	4 X R0.2	4	30	70	6	
New 2JJCR 025 001 250	2.5 X R0.1	2.5	25	60	4		2JJCR 040 002 350	4 X R0.2	4	35	75	6	
New 2JJCR 025 001 300	2.5 X R0.1	2.5	30	70	4		2JJCR 040 002 400	4 X R0.2	4	40	80	6	
2JJCR 025 002 100	2.5 X R0.2	2.5	10	50	4		2JJCR 040 003 120	4 X R0.3	4	12	50	6	
2JJCR 025 002 160	2.5 X R0.2	2.5	16	50	4		2JJCR 040 003 160	4 X R0.3	4	16	55	6	
2JJCR 025 002 200	2.5 X R0.2	2.5	20	50	4		2JJCR 040 003 200	4 X R0.3	4	20	60	6	
2JJCR 025 003 100	2.5 X R0.3	2.5	10	50	4		2JJCR 040 003 250	4 X R0.3	4	25	65	6	
2JJCR 025 003 160	2.5 X R0.3	2.5	16	50	4		2JJCR 040 003 300	4 X R0.3	4	30	70	6	
2JJCR 025 003 200	2.5 X R0.3	2.5	20	50	4		2JJCR 040 003 350	4 X R0.3	4	35	75	6	
2JJCR 025 005 100	2.5 X R0.5	2.5	10	50	4		2JJCR 040 003 400	4 X R0.3	4	40	80	6	
2JJCR 025 005 160	2.5 X R0.5	2.5	16	50	4		2JJCR 040 005 120	4 X R0.5	4	12	50	6	
2JJCR 025 005 200	2.5 X R0.5	2.5	20	50	4		2JJCR 040 005 160	4 X R0.5	4	16	55	6	
2JJCR 030 001 100	3 X R0.1	3	10	50	6		2JJCR 040 005 200	4 X R0.5	4	20	60	6	
2JJCR 030 001 120	3 X R0.1	3	12	50	6		2JJCR 040 005 250	4 X R0.5	4	25	65	6	
2JJCR 030 001 160	3 X R0.1	3	16	55	6		2JJCR 040 005 300	4 X R0.5	4	30	70	6	
2JJCR 030 001 200	3 X R0.1	3	20	60	6		2JJCR 040 005 350	4 X R0.5	4	35	75	6	
2JJCR 030 001 250	3 X R0.1	3	25	65	6		2JJCR 040 005 400	4 X R0.5	4	40	80	6	
2JJCR 030 001 300	3 X R0.1	3	30	70	6		2JJCR 040 010 120	4 X R1	4	12	50	6	
2JJCR 030 001 350	3 X R0.1	3	35	75	6		2JJCR 040 010 160	4 X R1	4	16	55	6	
2JJCR 030 001 400	3 X R0.1	3	40	80	6		2JJCR 040 010 200	4 X R1	4	20	60	6	
2JJCR 030 002 100	3 X R0.2	3	10	50	6		2JJCR 040 010 250	4 X R1	4	25	65	6	
2JJCR 030 002 120	3 X R0.2	3	12	50	6		2JJCR 040 010 300	4 X R1	4	30	70	6	
2JJCR 030 002 160	3 X R0.2	3	16	55	6		2JJCR 040 010 350	4 X R1	4	35	75	6	
2JJCR 030 002 200	3 X R0.2	3	20	60	6		2JJCR 040 010 400	4 X R1	4	40	80	6	
2JJCR 030 002 250	3 X R0.2	3	25	65	6		2JJCR 050 002 150	5 X R0.2	6	15	60	6	
2JJCR 030 002 300	3 X R0.2	3	30	70	6		2JJCR 050 002 250	5 X R0.2	6	25	70	6	
2JJCR 030 002 350	3 X R0.2	3	35	75	6		2JJCR 050 002 300	5 X R0.2	6	30	70	6	
2JJCR 030 002 400	3 X R0.2	3	40	80	6		2JJCR 050 002 400	5 X R0.2	6	40	80	6	
2JJCR 030 003 100	3 X R0.3	3	10	50	6		2JJCR 050 005 150	5 X R0.5	6	15	60	6	
2JJCR 030 003 120	3 X R0.3	3	12	50	6		2JJCR 050 005 250	5 X R0.5	6	25	70	6	
2JJCR 030 003 160	3 X R0.3	3	16	55	6		2JJCR 050 005 300	5 X R0.5	6	30	70	6	
2JJCR 030 003 200	3 X R0.3	3	20	60	6		2JJCR 050 005 400	5 X R0.5	6	40	80	6	
2JJCR 030 003 250	3 X R0.3	3	25	65	6		2JJCR 050 010 150	5 X R1	6	15	60	6	
2JJCR 030 003 300	3 X R0.3	3	30	70	6		2JJCR 050 010 250	5 X R1	6	25	70	6	
2JJCR 030 003 350	3 X R0.3	3	35	75	6		2JJCR 050 010 300	5 X R1	6	30	70	6	

단위 : mm

[illegible]

단위 : mm

[illegible]



R0.02 ~ 0.5 R1 ~ 1.5 R2 ~ 3

- 고정도강(HRC52~70), 프리하드강 계열의 고정밀가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 코너 R 형상을 날부치핑이 적도록 설계하였습니다.
- 다양한 코너R과 유효장으로 맞춤 가공이 가능합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- **Endmills for pre-hardened and hardened steel (HRc52~70)**
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Designed for minimizing edge chipping by corner R shape.
- Various corner R and flute length for wide range application.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.

D Size	D Tolerance
$\phi 0.5 \sim 5$	+0 ~ -0.01mm
$\phi 6 \sim 12$	-0.005 ~ -0.015mm

단위 : mm


Order Number	날경 Diameter D x R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샤프트 Shank Dia d	비고	Order Number	날경 Diameter D x R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샤프트 Shank Dia d	비고
New 4JJCR 005 0005 020	0.5 X R0.05	0.5	2	45	4		4JJCR 010 0005 100	1 X R0.05	1	10	50	4	
New 4JJCR 005 0005 040	0.5 X R0.05	0.5	4	45	4		4JJCR 010 0005 120	1 X R0.05	1	12	50	4	
New 4JJCR 005 0005 060	0.5 X R0.05	0.5	6	45	4		4JJCR 010 001 040	1 X R0.1	1	4	45	4	
New 4JJCR 005 0005 080	0.5 X R0.05	0.5	8	45	4		4JJCR 010 001 060	1 X R0.1	1	6	45	4	
New 4JJCR 005 001 020	0.5 X R0.1	0.5	2	45	4		4JJCR 010 001 080	1 X R0.1	1	8	45	4	
New 4JJCR 005 001 040	0.5 X R0.1	0.5	4	45	4		4JJCR 010 001 100	1 X R0.1	1	10	50	4	
New 4JJCR 005 001 060	0.5 X R0.1	0.5	6	45	4		4JJCR 010 001 120	1 X R0.1	1	12	50	4	
New 4JJCR 005 001 080	0.5 X R0.1	0.5	8	45	4		4JJCR 010 002 040	1 X R0.2	1	4	45	4	
New 4JJCR 006 0005 020	0.6 X R0.05	0.6	2	45	4		4JJCR 010 002 060	1 X R0.2	1	6	45	4	
New 4JJCR 006 0005 040	0.6 X R0.05	0.6	4	45	4		4JJCR 010 002 080	1 X R0.2	1	8	45	4	
New 4JJCR 006 0005 060	0.6 X R0.05	0.6	6	45	4		4JJCR 010 002 100	1 X R0.2	1	10	50	4	
New 4JJCR 006 0005 080	0.6 X R0.05	0.6	8	45	4		4JJCR 010 002 120	1 X R0.2	1	12	50	4	
New 4JJCR 006 001 020	0.6 X R0.1	0.6	2	45	4		4JJCR 010 003 040	1 X R0.3	1	4	45	4	
New 4JJCR 006 001 040	0.6 X R0.1	0.6	4	45	4		4JJCR 010 003 060	1 X R0.3	1	6	45	4	
New 4JJCR 006 001 060	0.6 X R0.1	0.6	6	45	4		4JJCR 010 003 080	1 X R0.3	1	8	45	4	
New 4JJCR 006 001 080	0.6 X R0.1	0.6	8	45	4		4JJCR 010 003 100	1 X R0.3	1	10	50	4	
New 4JJCR 007 0005 020	0.7 X R0.05	0.7	2	45	4		4JJCR 010 003 120	1 X R0.3	1	12	50	4	
New 4JJCR 007 0005 040	0.7 X R0.05	0.7	4	45	4		4JJCR 012 0002 040	1.2 X R0.02	1.2	4	45	4	
New 4JJCR 007 0005 060	0.7 X R0.05	0.7	6	45	4		4JJCR 012 0002 060	1.2 X R0.02	1.2	6	45	4	
New 4JJCR 007 0005 080	0.7 X R0.05	0.7	8	45	4		4JJCR 012 0002 080	1.2 X R0.02	1.2	8	45	4	
New 4JJCR 007 001 020	0.7 X R0.1	0.7	2	45	4		4JJCR 012 0002 100	1.2 X R0.02	1.2	10	50	4	
New 4JJCR 007 001 040	0.7 X R0.1	0.7	4	45	4		4JJCR 012 0002 120	1.2 X R0.02	1.2	12	50	4	
New 4JJCR 007 001 060	0.7 X R0.1	0.7	6	45	4		4JJCR 012 0005 040	1.2 X R0.05	1.2	4	45	4	
New 4JJCR 007 001 080	0.7 X R0.1	0.7	8	45	4		4JJCR 012 0005 060	1.2 X R0.05	1.2	6	45	4	
4JJCR 008 0002 020	0.8 X R0.02	0.8	2	45	4		4JJCR 012 0005 080	1.2 X R0.05	1.2	8	45	4	
4JJCR 008 0002 040	0.8 X R0.02	0.8	4	45	4		4JJCR 012 0005 100	1.2 X R0.05	1.2	10	50	4	
4JJCR 008 0002 060	0.8 X R0.02	0.8	6	45	4		4JJCR 012 0005 120	1.2 X R0.05	1.2	12	50	4	
4JJCR 008 0002 080	0.8 X R0.02	0.8	8	45	4		4JJCR 012 001 040	1.2 X R0.1	1.2	4	45	4	
4JJCR 008 0002 100	0.8 X R0.02	0.8	10	45	4		4JJCR 012 001 060	1.2 X R0.1	1.2	6	45	4	
4JJCR 008 0005 020	0.8 X R0.05	0.8	2	45	4		4JJCR 012 001 080	1.2 X R0.1	1.2	8	45	4	
4JJCR 008 0005 040	0.8 X R0.05	0.8	4	45	4		4JJCR 012 001 100	1.2 X R0.1	1.2	10	50	4	
4JJCR 008 0005 060	0.8 X R0.05	0.8	6	45	4		4JJCR 012 001 120	1.2 X R0.1	1.2	12	50	4	
4JJCR 008 0005 080	0.8 X R0.05	0.8	8	45	4		4JJCR 012 002 040	1.2 X R0.2	1.2	4	45	4	
4JJCR 008 0005 100	0.8 X R0.05	0.8	10	45	4		4JJCR 012 002 060	1.2 X R0.2	1.2	6	45	4	
4JJCR 008 001 020	0.8 X R0.1	0.8	2	45	4		4JJCR 012 002 080	1.2 X R0.2	1.2	8	45	4	
4JJCR 008 001 040	0.8 X R0.1	0.8	4	45	4		4JJCR 012 002 100	1.2 X R0.2	1.2	10	50	4	
4JJCR 008 001 060	0.8 X R0.1	0.8	6	45	4		4JJCR 012 002 120	1.2 X R0.2	1.2	12	50	4	
4JJCR 008 001 080	0.8 X R0.1	0.8	8	45	4		4JJCR 012 003 040	1.2 X R0.3	1.2	4	45	4	
4JJCR 008 001 100	0.8 X R0.1	0.8	10	45	4		4JJCR 012 003 060	1.2 X R0.3	1.2	6	45	4	
New 4JJCR 008 001 120	0.8 X R0.1	0.8	12	50	4		4JJCR 012 003 080	1.2 X R0.3	1.2	8	45	4	
4JJCR 010 0002 040	1 X R0.02	1	4	45	4		4JJCR 012 003 100	1.2 X R0.3	1.2	10	50	4	
4JJCR 010 0002 060	1 X R0.02	1	6	45	4		4JJCR 012 003 120	1.2 X R0.3	1.2	12	50	4	
4JJCR 010 0002 080	1 X R0.02	1	8	45	4		4JJCR 015 0002 060	1.5 X R0.02	1.5	6	45	4	
4JJCR 010 0002 100	1 X R0.02	1	10	50	4		4JJCR 015 0002 080	1.5 X R0.02	1.5	8	45	4	
4JJCR 010 0002 120	1 X R0.02	1	12	50	4		4JJCR 015 0002 100	1.5 X R0.02	1.5	10	50	4	
4JJCR 010 0005 040	1 X R0.05	1	4	45	4		4JJCR 015 0002 120	1.5 X R0.02	1.5	12	50	4	
4JJCR 010 0005 060	1 X R0.05	1	6	45	4		4JJCR 015 0002 160	1.5 X R0.02	1.5	16	50	4	
4JJCR 010 0005 080	1 X R0.05	1	8	45	4		4JJCR 015 0005 060	1.5 X R0.05	1.5	6	45	4	

단위 : mm

Order Number	날경 D x R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 D x R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
4JJCR 015 0005 080	1.5XR0.05	1.5	8	45	4		4JJCR 020 0005 120	2 X R0.5	2	12	50	4	
4JJCR 015 0005 100	1.5XR0.05	1.5	10	50	4		4JJCR 020 0005 160	2 X R0.5	2	16	50	4	
4JJCR 015 0005 120	1.5XR0.05	1.5	12	50	4		4JJCR 020 0005 200	2 X R0.5	2	20	50	4	
4JJCR 015 0005 160	1.5XR0.05	1.5	16	50	4		4JJCR 020 0005 250	2 X R0.5	2	25	60	4	
4JJCR 015 001 060	1.5 X R0.1	1.5	6	45	4		4JJCR 025 001 100	2.5 X R0.1	2.5	10	50	4	
4JJCR 015 001 080	1.5 X R0.1	1.5	8	45	4		4JJCR 025 001 160	2.5 X R0.1	2.5	16	50	4	
4JJCR 015 001 100	1.5 X R0.1	1.5	10	50	4		4JJCR 025 001 200	2.5 X R0.1	2.5	20	50	4	
4JJCR 015 001 120	1.5 X R0.1	1.5	12	50	4		4JJCR 025 001 250	2.5 X R0.1	2.5	25	60	4	
4JJCR 015 001 160	1.5 X R0.1	1.5	16	50	4		4JJCR 025 002 100	2.5 X R0.2	2.5	10	50	4	
4JJCR 015 002 060	1.5 X R0.2	1.5	6	45	4		4JJCR 025 002 160	2.5 X R0.2	2.5	16	50	4	
4JJCR 015 002 080	1.5 X R0.2	1.5	8	45	4		4JJCR 025 002 200	2.5 X R0.2	2.5	20	50	4	
4JJCR 015 002 100	1.5 X R0.2	1.5	10	50	4		4JJCR 025 002 250	2.5 X R0.2	2.5	25	60	4	
4JJCR 015 002 120	1.5 X R0.2	1.5	12	50	4		4JJCR 025 003 100	2.5 X R0.3	2.5	10	50	4	
4JJCR 015 002 160	1.5 X R0.2	1.5	16	50	4		4JJCR 025 003 160	2.5 X R0.3	2.5	16	50	4	
4JJCR 015 003 060	1.5 X R0.3	1.5	6	45	4		4JJCR 025 003 200	2.5 X R0.3	2.5	20	50	4	
4JJCR 015 003 080	1.5 X R0.3	1.5	8	45	4		4JJCR 025 003 250	2.5 X R0.3	2.5	25	60	4	
4JJCR 015 003 100	1.5 X R0.3	1.5	10	50	4		4JJCR 025 005 100	2.5 X R0.5	2.5	10	50	4	
4JJCR 015 003 120	1.5 X R0.3	1.5	12	50	4		4JJCR 025 005 160	2.5 X R0.5	2.5	16	50	4	
4JJCR 015 003 160	1.5 X R0.3	1.5	16	50	4		4JJCR 025 005 200	2.5 X R0.5	2.5	20	50	4	
4JJCR 015 005 060	1.5 X R0.5	1.5	6	45	4		4JJCR 025 005 250	2.5 X R0.5	2.5	25	60	4	
4JJCR 015 005 080	1.5 X R0.5	1.5	8	45	4		4JJCR 030 001 100	3 X R0.1	3	10	50	6	
4JJCR 015 005 100	1.5 X R0.5	1.5	10	50	4		4JJCR 030 001 120	3 X R0.1	3	12	50	6	
4JJCR 015 005 120	1.5 X R0.5	1.5	12	50	4		4JJCR 030 001 160	3 X R0.1	3	16	55	6	
4JJCR 015 005 160	1.5 X R0.5	1.5	16	50	4		4JJCR 030 001 200	3 X R0.1	3	20	60	6	
4JJCR 020 0002 060	2 X R0.02	2	6	45	4		4JJCR 030 001 250	3 X R0.1	3	25	65	6	
4JJCR 020 0002 080	2 X R0.02	2	8	45	4		4JJCR 030 001 300	3 X R0.1	3	30	70	6	
4JJCR 020 0002 100	2 X R0.02	2	10	50	4		4JJCR 030 001 350	3 X R0.1	3	35	75	6	
4JJCR 020 0002 120	2 X R0.02	2	12	50	4		4JJCR 030 002 100	3 X R0.2	3	10	50	6	
4JJCR 020 0002 160	2 X R0.02	2	16	50	4		4JJCR 030 002 120	3 X R0.2	3	12	50	6	
4JJCR 020 0002 200	2 X R0.02	2	20	50	4		4JJCR 030 002 160	3 X R0.2	3	16	55	6	
4JJCR 020 0002 250	2 X R0.02	2	25	60	4		4JJCR 030 002 200	3 X R0.2	3	20	60	6	
4JJCR 020 0005 060	2 X R0.05	2	6	45	4		4JJCR 030 002 250	3 X R0.2	3	25	65	6	
4JJCR 020 0005 080	2 X R0.05	2	8	45	4		4JJCR 030 002 300	3 X R0.2	3	30	70	6	
4JJCR 020 0005 100	2 X R0.05	2	10	50	4		4JJCR 030 002 350	3 X R0.2	3	35	75	6	
4JJCR 020 0005 120	2 X R0.05	2	12	50	4		New 4JJCR 030 002 400	3 X R0.2	3	40	80	6	
4JJCR 020 0005 160	2 X R0.05	2	16	50	4		4JJCR 030 003 100	3 X R0.3	3	10	50	6	
4JJCR 020 0005 200	2 X R0.05	2	20	50	4		4JJCR 030 003 120	3 X R0.3	3	12	50	6	
4JJCR 020 0005 250	2 X R0.05	2	25	60	4		4JJCR 030 003 160	3 X R0.3	3	16	55	6	
4JJCR 020 001 060	2 X R0.1	2	6	45	4		4JJCR 030 003 200	3 X R0.3	3	20	60	6	
4JJCR 020 001 080	2 X R0.1	2	8	45	4		4JJCR 030 003 250	3 X R0.3	3	25	65	6	
4JJCR 020 001 100	2 X R0.1	2	10	50	4		4JJCR 030 003 300	3 X R0.3	3	30	70	6	
4JJCR 020 001 120	2 X R0.1	2	12	50	4		4JJCR 030 003 350	3 X R0.3	3	35	75	6	
4JJCR 020 001 160	2 X R0.1	2	16	50	4		New 4JJCR 030 003 400	3 X R0.3	3	40	80	6	
4JJCR 020 001 200	2 X R0.1	2	20	50	4		4JJCR 030 005 100	3 X R0.5	3	10	50	6	
4JJCR 020 001 250	2 X R0.1	2	25	60	4		4JJCR 030 005 120	3 X R0.5	3	12	50	6	
4JJCR 020 002 060	2 X R0.2	2	6	45	4		4JJCR 030 005 160	3 X R0.5	3	16	55	6	
4JJCR 020 002 080	2 X R0.2	2	8	45	4		4JJCR 030 005 200	3 X R0.5	3	20	60	6	
4JJCR 020 002 100	2 X R0.2	2	10	50	4		4JJCR 030 005 250	3 X R0.5	3	25	65	6	
4JJCR 020 002 120	2 X R0.2	2	12	50	4		4JJCR 030 005 300	3 X R0.5	3	30	70	6	
4JJCR 020 002 160	2 X R0.2	2	16	50	4		4JJCR 030 005 350	3 X R0.5	3	35	75	6	
4JJCR 020 002 200	2 X R0.2	2	20	50	4		New 4JJCR 030 005 400	3 X R0.5	3	40	80	6	
4JJCR 020 002 250	2 X R0.2	2	25	60	4		4JJCR 030 010 100	3 X R1	3	10	50	6	
4JJCR 020 003 060	2 X R0.3	2	6	45	4		4JJCR 030 010 120	3 X R1	3	12	50	6	
4JJCR 020 003 080	2 X R0.3	2	8	45	4		4JJCR 030 010 160	3 X R1	3	16	55	6	
4JJCR 020 003 100	2 X R0.3	2	10	50	4		4JJCR 030 010 200	3 X R1	3	20	60	6	
4JJCR 020 003 120	2 X R0.3	2	12	50	4		4JJCR 030 010 250	3 X R1	3	25	65	6	
4JJCR 020 003 160	2 X R0.3	2	16	50	4		4JJCR 030 010 300	3 X R1	3	30	70	6	
4JJCR 020 003 200	2 X R0.3	2	20	50	4		4JJCR 030 010 350	3 X R1	3	35	75	6	
4JJCR 020 003 250	2 X R0.3	2	25	60	4		New 4JJCR 030 010 400	3 X R1	3	40	80	6	
4JJCR 020 005 060	2 X R0.5	2	6	45	4		4JJCR 040 001 130	4 X R0.1	4	13	55	6	
4JJCR 020 005 080	2 X R0.5	2	8	45	4		4JJCR 040 001 160	4 X R0.1	4	16	55	6	
4JJCR 020 005 100	2 X R0.5	2	10	50	4		4JJCR 040 001 200	4 X R0.1	4	20	60	6	

단위 : mm

Order Number	날경 Diameter D x R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter D x R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
4JJCR 040 001 250	4 X R0.1	4	25	65	6		New 4JJCR 060 005 500	6 X R0.5	7	50	100	6	
4JJCR 040 001 300	4 X R0.1	4	30	70	6		4JJCR 060 010 200	6 X R1	7	20	60	6	
4JJCR 040 001 350	4 X R0.1	4	35	75	6		4JJCR 060 010 400	6 X R1	7	40	80	6	
4JJCR 040 001 400	4 X R0.1	4	40	80	6		New 4JJCR 060 010 500	6 X R1	7	50	100	6	
4JJCR 040 002 130	4 X R0.2	4	13	55	6		4JJCR 060 015 200	6 X R1.5	7	20	60	6	
4JJCR 040 002 160	4 X R0.2	4	16	55	6		4JJCR 060 015 400	6 X R1.5	7	40	80	6	
4JJCR 040 002 200	4 X R0.2	4	20	60	6		New 4JJCR 080 002 220	8 X R0.2	9	22	65	8	
4JJCR 040 002 250	4 X R0.2	4	25	65	6		New 4JJCR 080 002 400	8 X R0.2	9	40	100	8	
4JJCR 040 002 300	4 X R0.2	4	30	70	6		4JJCR 080 003 220	8 X R0.3	9	22	65	8	
4JJCR 040 002 350	4 X R0.2	4	35	75	6		New 4JJCR 080 003 400	8 X R0.3	9	40	100	8	
4JJCR 040 002 400	4 X R0.2	4	40	80	6		4JJCR 080 005 220	8 X R0.5	9	22	65	8	
New 4JJCR 040 002 450	4 X R0.2	4	45	90	6		4JJCR 080 005 400	8 X R0.5	9	40	100	8	
New 4JJCR 040 002 500	4 X R0.2	4	50	100	6		New 4JJCR 080 005 500	8 X R0.5	9	50	120	8	
4JJCR 040 003 130	4 X R0.3	4	13	55	6		4JJCR 080 010 220	8 X R1	9	22	65	8	
4JJCR 040 003 160	4 X R0.3	4	16	55	6		4JJCR 080 010 400	8 X R1	9	40	100	8	
4JJCR 040 003 200	4 X R0.3	4	20	60	6		New 4JJCR 080 010 500	8 X R1	9	50	120	8	
4JJCR 040 003 250	4 X R0.3	4	25	65	6		4JJCR 080 015 220	8 X R1.5	9	22	65	8	
4JJCR 040 003 300	4 X R0.3	4	30	70	6		New 4JJCR 080 015 400	8 X R1.5	9	40	100	8	
4JJCR 040 003 350	4 X R0.3	4	35	75	6		4JJCR 080 020 220	8 X R2	9	22	65	8	
4JJCR 040 003 400	4 X R0.3	4	40	80	6		New 4JJCR 080 020 400	8 X R2	9	40	100	8	
New 4JJCR 040 003 450	4 X R0.3	4	45	90	6		New 4JJCR 080 020 500	8 X R2	9	50	120	8	
New 4JJCR 040 003 500	4 X R0.3	4	50	100	6		New 4JJCR 100 002 240	10 X R0.2	11	24	70	10	
4JJCR 040 005 130	4 X R0.5	4	13	55	6		New 4JJCR 100 002 400	10 X R0.2	11	40	100	10	
4JJCR 040 005 160	4 X R0.5	4	16	55	6		4JJCR 100 003 240	10 X R0.3	11	24	70	10	
4JJCR 040 005 200	4 X R0.5	4	20	60	6		New 4JJCR 100 003 400	10 X R0.3	11	40	100	10	
4JJCR 040 005 250	4 X R0.5	4	25	65	6		4JJCR 100 005 240	10 X R0.5	11	24	70	10	
4JJCR 040 005 300	4 X R0.5	4	30	70	6		4JJCR 100 005 400	10 X R0.5	11	40	100	10	
4JJCR 040 005 350	4 X R0.5	4	35	75	6		New 4JJCR 100 005 500	10 X R0.5	11	50	120	10	
4JJCR 040 005 400	4 X R0.5	4	40	80	6		4JJCR 100 010 240	10 X R1	11	24	70	10	
New 4JJCR 040 005 450	4 X R0.5	4	45	90	6		4JJCR 100 010 400	10 X R1	11	40	100	10	
New 4JJCR 040 005 500	4 X R0.5	4	50	100	6		New 4JJCR 100 010 500	10 X R1	11	50	120	10	
4JJCR 040 010 130	4 X R1	4	13	55	6		4JJCR 100 015 240	10 X R1.5	11	24	70	10	
4JJCR 040 010 160	4 X R1	4	16	55	6		New 4JJCR 100 015 400	10 X R1.5	11	40	100	10	
4JJCR 040 010 200	4 X R1	4	20	60	6		4JJCR 100 020 240	10 X R2	11	24	70	10	
4JJCR 040 010 250	4 X R1	4	25	65	6		New 4JJCR 100 020 400	10 X R2	11	40	100	10	
4JJCR 040 010 300	4 X R1	4	30	70	6		New 4JJCR 100 020 500	10 X R2	11	50	120	10	
4JJCR 040 010 350	4 X R1	4	35	75	6		4JJCR 100 025 240	10 X R2.5	11	24	70	10	
4JJCR 040 010 400	4 X R1	4	40	80	6		4JJCR 120 003 260	12 X R0.3	13	26	80	12	
New 4JJCR 040 010 450	4 X R1	4	45	90	6		4JJCR 120 005 260	12 X R0.5	13	26	80	12	
New 4JJCR 040 010 500	4 X R1	4	50	100	6		4JJCR 120 005 400	12 X R0.5	13	40	110	12	
4JJCR 050 001 160	5 X R0.1	5	16	60	6		New 4JJCR 120 005 600	12 X R0.5	13	60	130	12	
4JJCR 050 001 300	5 X R0.1	5	30	70	6		4JJCR 120 010 260	12 X R1	13	26	80	12	
4JJCR 050 002 160	5 X R0.2	5	16	60	6		4JJCR 120 010 400	12 X R1	13	40	110	12	
4JJCR 050 002 300	5 X R0.2	5	30	70	6		New 4JJCR 120 010 600	12 X R1	13	60	130	12	
4JJCR 050 003 160	5 X R0.3	5	16	60	6		4JJCR 120 015 260	12 X R1.5	13	26	80	12	
4JJCR 050 003 300	5 X R0.3	5	30	70	6		4JJCR 120 020 260	12 X R2	13	26	80	12	
4JJCR 050 005 160	5 X R0.5	5	16	60	6		New 4JJCR 120 020 400	12 X R2	13	40	110	12	
4JJCR 050 005 300	5 X R0.5	5	30	70	6		4JJCR 120 030 260	12 X R3	13	26	80	12	
New 4JJCR 050 005 400	5 X R0.5	5	40	80	6								
New 4JJCR 050 005 500	5 X R0.5	5	50	100	6								
4JJCR 050 010 160	5 X R1	5	16	60	6								
4JJCR 050 010 300	5 X R1	5	30	70	6								
New 4JJCR 050 010 400	5 X R1	5	40	80	6								
New 4JJCR 050 010 500	5 X R1	5	50	100	6								
4JJCR 060 001 200	6 X R0.1	7	20	60	6								
4JJCR 060 001 400	6 X R0.1	7	40	80	6								
4JJCR 060 002 200	6 X R0.2	7	20	60	6								
4JJCR 060 002 400	6 X R0.2	7	40	80	6								
4JJCR 060 003 200	6 X R0.3	7	20	60	6								
4JJCR 060 003 400	6 X R0.3	7	40	80	6								
4JJCR 060 005 200	6 X R0.5	7	20	60	6								
4JJCR 060 005 400	6 X R0.5	7	40	80	6								



- 고경도강(HRc52~70), 프리하든강 계열의 고속가공 엔드밀
- 고품질 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 코너R 형상을 날부치핑이 적도록 설계하였습니다.
- 다양한 코너R과 전장으로 맞춤 가공이 가능합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRc52~70)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Designed for minimizing edge chipping by corner R shape.
- Various corner R and overall length for wide range application.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.



D Size	D Tolerance
Ø0.2 ~ 5	+0 ~ -0.01mm
Ø6 ~ 12	-0.005 ~ -0.015mm

단위 : mm

Order Number	날경 Diameter D×R	날장 Length of cut L1	전장 Overall Length L	샤프트 Shank Dia d	비고
2JJC 002 0002 S04	0.2 X R0.02	0.4	45	4	
2JJC 002 0005 S04	0.2 X R0.05	0.4	45	4	
2JJC 003 0002 S04	0.3 X R0.02	0.6	45	4	
2JJC 003 0005 S04	0.3 X R0.05	0.6	45	4	
2JJC 003 001 S04	0.3 X R0.1	0.6	45	4	
2JJC 004 0002 S04	0.4 X R0.02	0.8	45	4	
2JJC 004 0005 S04	0.4 X R0.05	0.8	45	4	
2JJC 004 001 S04	0.4 X R0.1	0.8	45	4	
2JJC 005 0002 S04	0.5 X R0.02	1	45	4	
2JJC 005 0005 S04	0.5 X R0.05	1	45	4	
2JJC 005 001 S04	0.5 X R0.1	1	45	4	
2JJC 006 0002 S04	0.6 X R0.02	1.2	45	4	
2JJC 006 0005 S04	0.6 X R0.05	1.2	45	4	
2JJC 006 001 S04	0.6 X R0.1	1.2	45	4	
2JJC 006 002 S04	0.6 X R0.2	1.2	45	4	
2JJC 007 0005 S04	0.7 X R0.05	1.4	45	4	
2JJC 007 001 S04	0.7 X R0.1	1.4	45	4	
2JJC 007 002 S04	0.7 X R0.2	1.4	45	4	
2JJC 008 0002 S04	0.8 X R0.02	1.6	45	4	
2JJC 008 0005 S04	0.8 X R0.05	1.6	45	4	
2JJC 008 001 S04	0.8 X R0.1	1.6	45	4	
2JJC 008 002 S04	0.8 X R0.2	1.6	45	4	
2JJC 009 0005 S04	0.9 X R0.05	1.8	45	4	
2JJC 009 001 S04	0.9 X R0.1	1.8	45	4	
2JJC 010 0002 S04	1 X R0.02	2.5	45	4	
2JJC 010 0005 S04	1 X R0.05	2.5	45	4	
2JJC 010 001 S04	1 X R0.1	2.5	45	4	
2JJC 010 002 S04	1 X R0.2	2.5	45	4	
2JJC 010 003 S04	1 X R0.3	2.5	45	4	
2JJC 012 0002 S04	1.2 X R0.02	3.2	45	4	
2JJC 012 0005 S04	1.2 X R0.05	3.2	45	4	
2JJC 012 001 S04	1.2 X R0.1	3.2	45	4	
2JJC 012 002 S04	1.2 X R0.2	3.2	45	4	
2JJC 012 003 S04	1.2 X R0.3	3.2	45	4	
2JJC 015 0002 S04	1.5 X R0.02	4	45	4	
2JJC 015 0005 S04	1.5 X R0.05	4	45	4	
2JJC 015 001 S04	1.5 X R0.1	4	45	4	
2JJC 015 002 S04	1.5 X R0.2	4	45	4	
2JJC 015 003 S04	1.5 X R0.3	4	45	4	
2JJC 015 005 S04	1.5 X R0.5	4	45	4	
2JJC 020 0002 S04	2 X R0.02	6	45	4	
2JJC 020 0005 S04	2 X R0.05	6	45	4	
2JJC 020 001 S04	2 X R0.1	6	45	4	
2JJC 020 002 S04	2 X R0.2	6	45	4	
2JJC 020 003 S04	2 X R0.3	6	45	4	
2JJC 020 005 S04	2 X R0.5	6	45	4	
2JJC 025 001 S04	2.5 X R0.1	6	50	4	
2JJC 025 002 S04	2.5 X R0.2	6	50	4	


Order Number	날경 Diameter D×R	날장 Length of cut L1	전장 Overall Length L	샤프트 Shank Dia d	비고
2JJC 025 003 S04	2.5 X R0.3	6	50	4	
2JJC 025 005 S04	2.5 X R0.5	6	50	4	
2JJC 030 001 S06	3 X R0.1	8	60	6	
2JJC 030 002 S06	3 X R0.2	8	60	6	
2JJC 030 003 S06	3 X R0.3	8	60	6	
2JJC 030 005 S06	3 X R0.5	8	60	6	
2JJC 030 010 S06	3 X R1	8	60	6	
2JJC 040 001 S04	4 X R0.1	9	60	4	
2JJC 040 001 S06	4 X R0.1	10	70	6	
2JJC 040 002 S04	4 X R0.2	9	60	4	
2JJC 040 002 S06	4 X R0.2	10	70	6	
2JJC 040 003 S04	4 X R0.3	9	60	4	
2JJC 040 003 S06	4 X R0.3	10	70	6	
2JJC 040 005 S04	4 X R0.5	9	60	4	
2JJC 040 005 S06	4 X R0.5	10	70	6	
2JJC 040 010 S04	4 X R1	9	60	4	
2JJC 040 010 S06	4 X R1	10	70	6	
2JJC 050 001 S06	5 X R0.1	13	75	6	
2JJC 050 002 S06	5 X R0.2	13	75	6	
2JJC 050 003 S06	5 X R0.3	13	75	6	
2JJC 050 005 S06	5 X R0.5	13	75	6	
2JJC 050 010 S06	5 X R1	13	75	6	
2JJC 060 001 060	6 X R0.1	11	60	6	
2JJC 060 001 090	6 X R0.1	13	90	6	
2JJC 060 002 060	6 X R0.2	11	60	6	
2JJC 060 002 090	6 X R0.2	13	90	6	
2JJC 060 003 060	6 X R0.3	11	60	6	
2JJC 060 003 090	6 X R0.3	13	90	6	
2JJC 060 005 060	6 X R0.5	11	60	6	
2JJC 060 005 090	6 X R0.5	13	90	6	
New 2JJC 060 005 110	6 X R0.5	13	110	6	
2JJC 060 010 060	6 X R1	11	60	6	
2JJC 060 010 090	6 X R1	13	90	6	
New 2JJC 060 010 110	6 X R1	13	110	6	
2JJC 060 015 060	6 X R1.5	11	60	6	
2JJC 060 015 090	6 X R1.5	13	90	6	
2JJC 060 020 060	6 X R2	11	60	6	
2JJC 060 020 090	6 X R2	13	90	6	
2JJC 060 025 090	6 X R2.5	13	90	6	
2JJC 080 001 070	8 X R0.1	16	70	8	
2JJC 080 001 100	8 X R0.1	19	100	8	
2JJC 080 002 070	8 X R0.2	16	70	8	
2JJC 080 002 100	8 X R0.2	19	100	8	
2JJC 080 003 070	8 X R0.3	16	70	8	
2JJC 080 003 100	8 X R0.3	19	100	8	
2JJC 080 005 070	8 X R0.5	16	70	8	
2JJC 080 005 100	8 X R0.5	19	100	8	
New 2JJC 080 005 120	8 X R0.5	19	120	8	



단위 : mm

Order Number	날경 Diameter D x R	날장 Length of cut L1	전장 Overall Length L	샙크 Shank Dia d	비고	Order Number	날경 Diameter D x R	날장 Length of cut L1	전장 Overall Length L	샙크 Shank Dia d	비고
2JJC 080 010 070	8 X R1	16	70	8		2JJC 120 040 110	12 X R4	26	110	12	
2JJC 080 010 100	8 X R1	19	100	8		2JJC 120 050 110	12 X R5	26	110	12	
New 2JJC 080 010 120	8 X R1	19	120	8							
2JJC 080 015 070	8 X R1.5	16	70	8							
2JJC 080 015 100	8 X R1.5	19	100	8							
2JJC 080 020 070	8 X R2	16	70	8							
2JJC 080 020 100	8 X R2	19	100	8							
2JJC 080 025 100	8 X R2.5	19	100	8							
2JJC 080 030 100	8 X R3	19	100	8							
2JJC 080 035 100	8 X R3.5	19	100	8							
2JJC 100 001 075	10 X R0.1	19	75	10							
2JJC 100 001 100	10 X R0.1	22	100	10							
2JJC 100 002 075	10 X R0.2	19	75	10							
2JJC 100 002 100	10 X R0.2	22	100	10							
2JJC 100 003 075	10 X R0.3	19	75	10							
2JJC 100 003 100	10 X R0.3	22	100	10							
2JJC 100 005 075	10 X R0.5	19	75	10							
2JJC 100 005 100	10 X R0.5	22	100	10							
New 2JJC 100 005 120	10 X R0.5	22	120	10							
2JJC 100 010 075	10 X R1	19	75	10							
2JJC 100 010 100	10 X R1	22	100	10							
New 2JJC 100 010 120	10 X R1	22	120	10							
2JJC 100 015 075	10 X R1.5	19	75	10							
2JJC 100 015 100	10 X R1.5	22	100	10							
2JJC 100 020 075	10 X R2	19	75	10							
2JJC 100 020 100	10 X R2	22	100	10							
2JJC 100 025 100	10 X R2.5	22	100	10							
2JJC 100 030 100	10 X R3	22	100	10							
2JJC 100 040 100	10 X R4	22	100	10							
2JJC 120 001 080	12 X R0.1	22	80	12							
2JJC 120 001 110	12 X R0.1	26	110	12							
2JJC 120 002 080	12 X R0.2	22	80	12							
2JJC 120 002 110	12 X R0.2	26	110	12							
2JJC 120 003 080	12 X R0.3	22	80	12							
2JJC 120 003 110	12 X R0.3	26	110	12							
2JJC 120 005 080	12 X R0.5	22	80	12							
2JJC 120 005 110	12 X R0.5	26	110	12							
New 2JJC 120 005 130	12 X R0.5	26	130	12							
2JJC 120 010 080	12 X R1	22	80	12							
2JJC 120 010 110	12 X R1	26	110	12							
New 2JJC 120 010 130	12 X R1	26	130	12							
2JJC 120 015 080	12 X R1.5	22	80	12							
2JJC 120 015 110	12 X R1.5	26	110	12							
2JJC 120 020 080	12 X R2	22	80	12							
2JJC 120 020 110	12 X R2	26	110	12							
New 2JJC 120 020 130	12 X R2	26	130	12							
2JJC 120 025 110	12 X R2.5	26	110	12							
2JJC 120 030 110	12 X R3	26	110	12							

4날 고정도재 가공용 제이제이 코너 레디우스 엔드밀



- 고정도강(HRc52~70), 프리하든강 계열의 고속가공 엔드밀
- 고품량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 고정밀 공차 적용으로 초정밀 가공에 적합합니다.
- 코너R 형상을 날부치핑이 적도록 설계하였습니다.
- 다양한 코너R과 전장으로 맞춤 가공이 가능합니다.
- 초미립자 초경합금(0.2 μ m)을 채택, 고속절삭시 뛰어난 성능을 발휘합니다.
- Endmills for pre-hardened and hardened steel(HRc52~70)
- Good wear resistance by high quality Si-based PVD coating.
- High precise edge tolerance.
- Designed for minimizing edge chipping by corner R shape.
- Various corner R and overall length for wide range application.
- Outstanding performance at high speed machining by ultra fine (0.2 μ m) WC grade.



D Size	D Tolerance
Ø0.5 ~ 5	+0 ~ -0.01mm
Ø6 ~ 16	-0.005 ~ -0.015mm


단위 : mm

Order Number	날경 Diameter D x R	날장 Length of cut L1	전장 Overall Length L	생크 Shank Dia d	비고	Order Number	날경 Diameter D x R	날장 Length of cut L1	전장 Overall Length L	생크 Shank Dia d	비고
New 4JJC 005 0005 S04	0.5 X R0.05	1	45	4		4JJC 045 005 S06	4.5 X R0.5	11	75	6	
New 4JJC 005 001 S04	0.5 X R0.1	1	45	4		4JJC 050 001 S06	5 X R0.1	13	75	6	
New 4JJC 006 0005 S04	0.6 X R0.05	1.2	45	4		4JJC 050 002 S06	5 X R0.2	13	75	6	
New 4JJC 006 001 S04	0.6 X R0.1	1.2	45	4		4JJC 050 003 S06	5 X R0.3	13	75	6	
New 4JJC 007 0005 S04	0.7 X R0.05	1.4	45	4		4JJC 050 005 S06	5 X R0.5	13	75	6	
New 4JJC 007 001 S04	0.7 X R0.1	1.4	45	4		4JJC 050 010 S06	5 X R1	13	75	6	
New 4JJC 008 0005 S04	0.8 X R0.05	1.6	45	4		4JJC 060 0005 055	6 X R0.05	11	55	6	
New 4JJC 008 001 S04	0.8 X R0.1	1.6	45	4		4JJC 060 0005 080	6 X R0.05	13	80	6	
New 4JJC 009 0005 S04	0.9 X R0.05	1.8	45	4		4JJC 060 001 055	6 X R0.1	11	55	6	
New 4JJC 009 001 S04	0.9 X R0.1	1.8	45	4		4JJC 060 001 080	6 X R0.1	13	80	6	
4JJC 010 0005 S04	1 X R0.05	2.5	45	4		4JJC 060 002 055	6 X R0.2	11	55	6	
4JJC 010 001 S04	1 X R0.1	2.5	45	4		4JJC 060 002 080	6 X R0.2	13	80	6	
4JJC 010 002 S04	1 X R0.2	2.5	45	4		New 4JJC 060 002 100	6 X R0.2	13	100	6	
4JJC 010 003 S04	1 X R0.3	2.5	45	4		New 4JJC 060 002 120	6 X R0.2	13	120	6	
4JJC 015 0005 S04	1.5 X R0.05	4	45	4		4JJC 060 003 055	6 X R0.3	11	55	6	
4JJC 015 001 S04	1.5 X R0.1	4	45	4		4JJC 060 003 080	6 X R0.3	13	80	6	
4JJC 015 002 S04	1.5 X R0.2	4	45	4		New 4JJC 060 003 100	6 X R0.3	13	100	6	
4JJC 015 003 S04	1.5 X R0.3	4	45	4		New 4JJC 060 003 120	6 X R0.3	13	120	6	
4JJC 015 005 S04	1.5 X R0.5	4	45	4		4JJC 060 005 055	6 X R0.5	11	55	6	
4JJC 020 0005 S04	2 X R0.05	6	45	4		4JJC 060 005 080	6 X R0.5	13	80	6	
4JJC 020 001 S04	2 X R0.1	6	45	4		New 4JJC 060 005 100	6 X R0.5	13	100	6	
4JJC 020 002 S04	2 X R0.2	6	45	4		New 4JJC 060 005 120	6 X R0.5	13	120	6	
4JJC 020 003 S04	2 X R0.3	6	45	4		4JJC 060 010 055	6 X R1	11	55	6	
4JJC 020 005 S04	2 X R0.5	6	45	4		4JJC 060 010 080	6 X R1	13	80	6	
4JJC 025 001 S04	2.5 X R0.1	6	50	4		New 4JJC 060 010 100	6 X R1	13	100	6	
4JJC 025 002 S04	2.5 X R0.2	6	50	4		New 4JJC 060 010 120	6 X R1	13	120	6	
4JJC 025 003 S04	2.5 X R0.3	6	50	4		4JJC 060 015 055	6 X R1.5	11	55	6	
4JJC 025 005 S04	2.5 X R0.5	6	50	4		4JJC 060 015 080	6 X R1.5	13	80	6	
4JJC 030 001 S06	3 X R0.1	8	60	6		4JJC 060 020 055	6 X R2	11	55	6	
4JJC 030 002 S06	3 X R0.2	8	60	6		4JJC 060 020 080	6 X R2	13	80	6	
4JJC 030 003 S06	3 X R0.3	8	60	6		New 4JJC 080 002 060	8 X R0.2	16	60	8	
4JJC 030 005 S06	3 X R0.5	8	60	6		New 4JJC 080 002 090	8 X R0.2	19	90	8	
4JJC 030 010 S06	3 X R1	8	60	6		4JJC 080 003 060	8 X R0.3	16	60	8	
4JJC 035 001 S06	3.5 X R0.1	9	70	6		4JJC 080 003 090	8 X R0.3	19	90	8	
4JJC 035 002 S06	3.5 X R0.2	9	70	6		4JJC 080 005 060	8 X R0.5	16	60	8	
4JJC 035 003 S06	3.5 X R0.3	9	70	6		4JJC 080 005 090	8 X R0.5	19	90	8	
4JJC 035 005 S06	3.5 X R0.5	9	70	6		New 4JJC 080 005 110	8 X R0.5	19	110	8	
4JJC 040 001 S04	4 X R0.1	9	60	4		New 4JJC 080 005 150	8 X R0.5	19	150	8	
4JJC 040 001 S06	4 X R0.1	10	70	6		4JJC 080 010 060	8 X R1	16	60	8	
4JJC 040 002 S04	4 X R0.2	9	60	4		4JJC 080 010 090	8 X R1	19	90	8	
4JJC 040 002 S06	4 X R0.2	10	70	6		New 4JJC 080 010 110	8 X R1	19	110	8	
4JJC 040 003 S04	4 X R0.3	9	60	4		New 4JJC 080 010 150	8 X R1	19	150	8	
4JJC 040 003 S06	4 X R0.3	10	70	6		4JJC 080 015 060	8 X R1.5	16	60	8	
4JJC 040 005 S04	4 X R0.5	9	60	4		4JJC 080 015 090	8 X R1.5	19	90	8	
4JJC 040 005 S06	4 X R0.5	10	70	6		4JJC 080 020 060	8 X R2	16	60	8	
4JJC 040 010 S04	4 X R1	9	60	4		4JJC 080 020 090	8 X R2	19	90	8	
4JJC 040 010 S06	4 X R1	10	70	6		New 4JJC 100 002 070	10 X R0.2	19	70	10	
4JJC 045 002 S06	4.5 X R0.2	11	75	6		New 4JJC 100 002 100	10 X R0.2	22	100	10	



단위 : mm

Order Number	날경 Diameter D × R	날장 Length of cut L1	전장 Overall Length L	생크 Shank Dia d	비고						
4JJC 100 003 070	10 X R0.3	19	70	10							
4JJC 100 003 100	10 X R0.3	22	100	10							
4JJC 100 005 070	10 X R0.5	19	70	10							
4JJC 100 005 100	10 X R0.5	22	100	10							
New 4JJC 100 005 120	10 X R0.5	22	120	10							
New 4JJC 100 005 150	10 X R0.5	22	150	10							
4JJC 100 010 070	10 X R1	19	70	10							
4JJC 100 010 100	10 X R1	22	100	10							
New 4JJC 100 010 120	10 X R1	22	120	10							
New 4JJC 100 010 150	10 X R1	22	150	10							
4JJC 100 015 070	10 X R1.5	19	70	10							
4JJC 100 015 100	10 X R1.5	22	100	10							
4JJC 100 020 070	10 X R2	19	70	10							
4JJC 100 020 100	10 X R2	22	100	10							
New 4JJC 100 020 120	10 X R2	22	120	10							
New 4JJC 100 020 150	10 X R2	22	150	10							
4JJC 100 025 070	10 X R2.5	19	70	10							
4JJC 100 025 100	10 X R2.5	22	100	10							
New 4JJC 120 002 075	12 X R0.2	22	75	12							
New 4JJC 120 002 110	12 X R0.2	26	110	12							
4JJC 120 003 075	12 X R0.3	22	75	12							
4JJC 120 003 110	12 X R0.3	26	110	12							
4JJC 120 005 075	12 X R0.5	22	75	12							
4JJC 120 005 110	12 X R0.5	26	110	12							
New 4JJC 120 005 130	12 X R0.5	26	130	12							
New 4JJC 120 005 160	12 X R0.5	26	160	12							
4JJC 120 010 075	12 X R1	22	75	12							
4JJC 120 010 110	12 X R1	26	110	12							
New 4JJC 120 010 130	12 X R1	26	130	12							
New 4JJC 120 010 160	12 X R1	26	160	12							
4JJC 120 015 075	12 X R1.5	22	75	12							
4JJC 120 015 110	12 X R1.5	26	110	12							
4JJC 120 020 075	12 X R2	22	75	12							
4JJC 120 020 110	12 X R2	26	110	12							
New 4JJC 120 020 130	12 X R2	26	130	12							
New 4JJC 120 020 160	12 X R2	26	160	12							
4JJC 120 025 075	12 X R2.5	22	75	12							
4JJC 120 025 110	12 X R2.5	26	110	12							
4JJC 120 030 075	12 X R3	22	75	12							
4JJC 120 030 110	12 X R3	26	110	12							
New 4JJC 160 005 110	16 X R0.5	32	110	16							
New 4JJC 160 010 110	16 X R1	32	110	16							



- **고경도강(HRc52~70), 프리하드강 계열의 고정밀가공 엔드밀**
- 고풍량 실리콘계 코팅(Si) 처리하여 내마모성이 우수합니다.
- 저속 RPM에서 고이송 작업이 가능 하도록 설계하였습니다.
- 중삭 및 황삭 가공시 작업 효율이 극대화 됩니다.
- 항절력이 높은 초미립자 초경합금을 채택하여, 고이송 작업시 엔드밀의 파손을 최소화 하였습니다.
- **Endmills for pre-hardened and hardened steel(HRc52~70)**
- Good wear resistance by high quality Si-based PVD coating.
- Designed for low speed with high feed condition.
- Suitable for heavy duty and roughing application.
- Minimize fracturing at high feed by high TRS ultra fine WC grade.

D Size	D Tolerance
1 ~ 5 ϕ	+0 ~ -0.01mm
6 ~ 12 ϕ	-0.005 ~ -0.015mm
16 ϕ	-0.01 ~ -0.02mm

단위 : mm

Order Number	날경 Diameter D × R	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크 Shank Dia d	비고
4JJRC 010 002 025	1 X R0.2	1	2.5	50	4	
4JJRC 015 005 040	1.5 X R0.5	1.5	4	50	4	
4JJRC 020 005 060	2 X R0.5	2	6	50	6	
4JJRC 030 005 080	3 X R0.5	3	8	50	6	
4JJRC 040 005 120	4 X R0.5	4	12	60	6	
4JJRC 040 005 160	4 X R0.5	4	16	60	6	
4JJRC 040 010 120	4 X R1	4	12	60	6	
4JJRC 040 010 160	4 X R1	4	16	60	6	
4JJRC 050 005 150	5 X R0.5	5	15	60	6	
4JJRC 050 010 150	5 X R1	5	15	60	6	
4JJRC 060 003 150	6 X R0.3	6	15	60	6	
4JJRC 060 005 150	6 X R0.5	6	15	60	6	
4JJRC 060 010 150	6 X R1	6	15	60	6	
4JJRC 060 015 150	6 X R1.5	6	15	60	6	
4JJRC 080 003 160	8 X R0.3	8	16	60	8	
4JJRC 080 005 160	8 X R0.5	8	16	60	8	
4JJRC 080 005 200	8 X R0.5	8	20	80	8	
4JJRC 080 005 300	8 X R0.5	8	30	110	8	
4JJRC 080 010 160	8 X R1	8	16	60	8	
4JJRC 080 010 200	8 X R1	8	20	80	8	
4JJRC 080 010 300	8 X R1	8	30	110	8	
4JJRC 080 020 160	8 X R2	8	16	60	8	
4JJRC 080 020 200	8 X R2	8	20	80	8	
4JJRC 080 020 300	8 X R2	8	30	110	8	
4JJRC 100 003 200	10 X R0.3	10	20	70	10	
4JJRC 100 005 200	10 X R0.5	10	20	70	10	
4JJRC 100 005 250	10 X R0.5	10	25	90	10	
4JJRC 100 005 300	10 X R0.5	10	30	120	10	
4JJRC 100 010 200	10 X R1	10	20	70	10	
4JJRC 100 010 250	10 X R1	10	25	90	10	
4JJRC 100 010 300	10 X R1	10	30	120	10	
4JJRC 100 020 200	10 X R2	10	20	70	10	
4JJRC 100 020 250	10 X R2	10	25	90	10	
4JJRC 100 020 300	10 X R2	10	30	120	10	
4JJRC 120 005 250	12 X R0.5	12	25	80	12	
4JJRC 120 005 300	12 X R0.5	12	30	100	12	
4JJRC 120 005 350	12 X R0.5	12	35	130	12	
4JJRC 120 010 250	12 X R1	12	25	80	12	
4JJRC 120 010 300	12 X R1	12	30	100	12	
4JJRC 120 010 350	12 X R1	12	35	130	12	
4JJRC 120 020 250	12 X R2	12	25	80	12	
4JJRC 120 020 300	12 X R2	12	30	100	12	
4JJRC 120 020 350	12 X R2	12	35	130	12	
4JJRC 120 030 250	12 X R3	12	25	80	12	
4JJRC 160 010 300	16 X R1	16	30	110	16	
4JJRC 160 010 400	16 X R1	16	40	160	16	
4JJRC 160 020 300	16 X R2	16	30	110	16	
4JJRC 160 020 400	16 X R2	16	40	160	16	

[illegible]